## DEWALT

## **20V MAX\* IMPACT WRENCHES**

XR® Brushless 1/2" High Torque Impact Wrench with Detent Pin Anvil





20v X	SA=

**SPECIFICATIONS** Voltage 20V MAX Drive Size 1/2" 700 ft-lbs Max Torque (Tightening) Max Breakaway Torque 1200 ft-lbs Anvil Type Detent Pin No Load Speed 0-400/0-1200/0-1900 rpm Impacts / Minute 0-2400 ipm LED Yes Tool Length 8-13/16" Tool Weight (Tool only) 5.8 lbs

AVAILABLE		
DCF899B	Batteries and Charger Sold Separately	
DCF899P2	Also Includes: (2) 20V MAX* XR® Lithium Ion Batteries (5.0 Ah), Charger, and Kit Bag	
n-matr		

DCF899P2

XR® Brushless 1/2" High Torque Impact Wrench with Hog Ring Anvil

DCF899HB



20v	X	USA=

SPECIFICATIONS	
Voltage	20V MAX*
Drive Size	1/2"
Max Torque (Tightening)	700 ft-lbs
Max Breakaway Torque	1200 ft-lbs
Anvil Type	Hog Ring
No Load Speed	0-400/0-1200/0-1900 rpm
Impacts / Minute	0-2400 ipm
LED	Yes
Tool Length	8-13/16"
Tool Weight (Tool only)	5.8 lbs

AVAILABLE		
DCF899HB	Batteries and Charger Sold Separately	
DCF899HP2	Also Includes: (2) 20V MAX* $XR^{\otimes}$ Lithium Ion Batteries (5.0 Ah), Charger, and Kit Bag	



DCF899HP2

XR® Brushless 3/4" High Torque Impact Wrench with Hog Ring Anvil





**SPECIFICATIONS** 20V MAX\* Drive Size 3/4" Max Torque (Tightening) 700 ft-lbs Max Breakaway Torque 1200 ft-lbs Anvil Type Hog Ring No Load Speed 0-400/0-1200/0-1900 rpm Impacts / Minute 0-2400 ipm LED Tool Length 8-13/16" Tool Weight (Tool only) 5.8 lbs

AVAILABLE	
DCF897B	Batteries and Charger Sold Separately
DCF897P2	Also Includes: (2) 20V MAX* XR® Lithium Ion Batteries (5.0 Ah), Charger, and Kit Bag



DCF897P2

XR® Brushless 7/16" High **Torque Impact Wrench with Quick Release Chuck** 



COMMX / 10:	MADE IN THE * * * * *
207 > X	IIGV=
LITTHE IM ION DOLLSHIESS	US/A
	WITH GLOBAL MATERIALS

SPECIFICATIONS	
Voltage	20V MAX*
Drive Size	7/16"
Max Torque (Tightening)	700 ft-lbs
Max Breakaway Torque	1200 ft-lbs
Chuck Type	Quick Release
No Load Speed	0-400/0-1200/0-1900 rpm
Impacts / Minute	0-2400 ipm
LED	Yes
Tool Length	8-13/16"

SPECIFICATIONS	
Voltage	20V MAX*
Drive Size	7/16"
Max Torque (Tightening)	700 ft-lbs
Max Breakaway Torque	1200 ft-lbs
Chuck Type	Quick Release
No Load Speed	0-400/0-1200/0-1900 rpm
Impacts / Minute	0-2400 ipm
LED	Yes
Tool Length	8-13/16"
Tool Weight (Tool only)	5.8 lbs

AVAILABLE	
DCF898B	Batteries and Charger Sold Separately
DCF898P2	Also Includes: (2) 20V MAX* $\rm XR^{\odot}$ Lithium Ion Batteries (5.0 Ah), Charger, and Kit Bag



DCF898P2

XR® Brushless 1/2" Mid-Range Impact Wrench with Detent Pin Anvil



	8
20V	USA WITH GLOOL MATERIALS

SPECIFICATIONS	
Voltage	20V MAX*
Drive Size	1/2"
Max Torque (Tightening)	330 ft-lbs
Max Breakaway Torque	600 ft-lbs
Anvil Type	Detent Pin
No Load Speed	0-900/0-2000 rpm
Impacts / Minute	0-3100 ipm
LED	Yes
Tool Length	7"
Tool Weight (Tool only)	3.5 lbs
to study a	D-8-111-

AVAILABLE	
DCF894B	Batteries and Charger Sold Separately
DCF894P2	Also Includes: (2) 20V MAX* XR® Lithium Ion Batteries (5.0 Ah), Charger, and Kit Bag



DCF894P2