

## SDS PLUS DUST TRAP™ DRILLING SHROUD

### OVERVIEW

The MILWAUKEE® SDS Plus DUST TRAP™ is the industry's first OSHA® compliance solution without a vacuum, ideal for overhead drilling applications. The universal fit allows the DUST TRAP™ to work with all SDS Plus rotary hammers and SDS Plus drill bits up to an 8" length, including stop bits and other anchor installations tools. The clear sleeve allows visibility while the locking mechanism enables easy storage on the jobsite. The compact, collapsible design is ideal for tough to reach places, providing superior productivity. The DUST TRAP™ is an OSHA® Objective Data compliance solution when used without a vacuum and OSHA® Table 1 compliant when used with a dust extractor, giving users the flexibility to adjust to the daily demands of the jobsite while being compliant. Replacement SDS Plus DUST TRAP™ Sleeves are available (48-03-3235).



### FEATURES

- OSHA® Objective Data compliance without a vacuum
- Universal fit on SDS Plus rotary hammers and drill bits up to 8" long
- Preferred Table 1 solution for the OSHA® Regulation on Crystalline Silica Dust (29CFR 1926.1153), when used with a dust extractor

### SDS PLUS DUST TRAP™ DRILLING SHROUD

| Description                            | 1 Pack     | 5 Pack     | 10 Pack    |
|--|------------|------------|------------|
| SDS Plus DUST TRAP™ Drilling Shroud    | 48-03-3035 | -          | 48-03-3135 |
| SDS Plus DUST TRAP™ Replacement Sleeve | -          | 48-03-3235 | -          |

## SDS PLUS VACUUM BITS

### OVERVIEW

The MILWAUKEE® SDS Plus Vacuum Drill Bits reduce airborne silica dust and provide increased productivity during the chemical anchor preparation process. The combination of dust extraction holes at the bit tip and the hollow shaft design allow dust to be removed through the bit while drilling holes, reducing airborne silica dust in the process. SDS Plus Vacuum Drill Bits are an OSHA® Table 1 compliant solution when used with dust extraction vacuums. Additionally, SDS Plus Vacuum Drill Bits leave clean holes which are ready for the chemical anchor installation, removing the need to use standard drill bits with the "blow-brush-blow" cleaning method, delivering up to 2X faster chemical anchor preparation. The 4-Cutter tip design delivers durability in concrete and concrete with rebar applications. The universal adapter fits most common dust extractor attachments.



### FEATURES

- Drilling holes into brick, block, concrete, and concrete with rebar
- Preferred Table 1 solution for the OSHA® Regulation on Crystalline Silica Dust (29 CFR 1926.1153), when used with a dust extractor
- Up to 2X faster chemical anchor preparation

UP TO  
**2X** FASTER CHEMICAL  
ANCHOR PREP

### SDS PLUS VACUUM BITS

| Diameter | Usable Length | Length | Part No.   |
|----------|---------------|--------|------------|
| 7/16"    | 7-7/8"        | 13"    | 48-20-2102 |
| 1/2"     | 7-7/8"        | 13"    | 48-20-2106 |
| 9/16"    | 9-1/2"        | 14"    | 48-20-2110 |
| 5/8"     | 9-1/2"        | 14"    | 48-20-2114 |
| 3/4"     | 9-1/2"        | 14"    | 48-20-2118 |



This product complies with ANSI B212.15 standard

### SDS PLUS VACUUM BITS ADAPTER

| Description                  | Part No.   |
|------------------------------|------------|
| SDS Plus Vacuum Bits Adapter | 48-20-2100 |

## SDS PLUS TWO-PIECE CORE BITS

### OVERVIEW

MILWAUKEE's SDS Plus Two-piece Core Bits are ideal for drilling large through holes into brick, block, and concrete. Two-piece design allows for system versatility.



### FEATURES

- Thin Wall Design
- Two-Piece Design for versatility
- Ability to use extensions

### SDS PLUS TWO-PIECE CORE BITS

| Size   | Depth    | Core Body with Guide Plate and Centering Pin Part No. | 8" SDS Plus Adapter Shank Part No. | 12" SDS Plus Adapter Shank Part No. | 7-1/2" Extension Part No. | Replacement Guide Plate Part No. | Replacement Centering Pin Part No. |
|--------|----------|---|------------------------------------|-------------------------------------|---------------------------|----------------------------------|------------------------------------|
| 1"     | 3-3/16"  | 48-20-5005*   | 48-03-3545                         | 48-03-3551                          | 48-95-6070                | -                                | -                                  |
| 1-1/8" | 3-3/16"  | 48-20-5010*   | 48-03-3545                         | 48-03-3551                          | 48-95-6070                | -                                | -                                  |
| 1-1/4" | 3-3/16"  | 48-20-5015  | 48-03-3545                         | 48-03-3551                          | 48-95-6070                | 48-20-6151                       | 48-20-6150                         |
| 1-3/8" | 3-3/16"  | 48-20-5020  | 48-03-3545                         | 48-03-3551                          | 48-95-6070                | 48-20-6152                       | 48-20-6150                         |
| 1-1/2" | 3-3/16"  | 48-20-5025  | 48-03-3545                         | 48-03-3551                          | 48-95-6070                | 48-20-6153                       | 48-20-6150                         |
| 1-3/4" | 2-13/16" | 48-20-5030  | 48-03-3555                         | 48-03-3561                          | 48-95-6075                | 48-20-6156                       | 48-20-6155                         |
| 2"     | 2-13/16" | 48-20-5035  | 48-03-3555                         | 48-03-3561                          | 48-95-6075                | 48-20-6157                       | 48-20-6155                         |
| 2-1/2" | 2-13/16" | 48-20-5040  | 48-03-3555                         | 48-03-3561                          | 48-95-6075                | 48-20-6158                       | 48-20-6155                         |
| 3"     | 2-13/16" | 48-20-5045  | 48-03-3555                         | 48-03-3561                          | 48-95-6075                | 48-20-6159                       | 48-20-6155                         |
| 3-1/2" | 2-13/16" | 48-20-5050  | 48-03-3555                         | 48-03-3561                          | 48-95-6075                | 48-20-6160                       | 48-20-6155                         |
| 4"     | 2-13/16" | 48-20-5055  | 48-03-3555                         | 48-03-3561                          | 48-95-6075                | 48-20-6161                       | 48-20-6155                         |

\*Guide plate and centering pin not included with 1" and 1-1/8" diameter core bits