
Adjustable I-Beam Adapter – CSBS3





- Meets requirements of the Buy American Act
- No loose parts
- No assembly required
- Snap-off bolt head helps enable easy installation and inspection of seismic sway braces
- Meets NFPA®-13 requirements for seismic sway bracing







Part Number	CSBS3
Material	Steel
Finish	Electrogalvanized
Flange Thickness (FT)	1/4" - 3/4"
А	4" - 8 1/2"
Rod Size 1 (RS1)	3/8"
Rod Size 2 (RS2)	1/2"
Height (H)	2 5/8"
Width (W)	3 5/8"
Certifications	cULus FM Tested FM, Seismic OSHPD
Standard Packaging Quantity	10 рс
UPC	78285692011
EAN-13	0782856920113



UL Loads									
Part Number	Flange Thickness	Perpendicular to Structure	Parallel to Structure						
CSBS3	1/4" - 3/8"	3,000 lb	2,200 lb						
	3/8" - 3/4"	3,000 lb	2,765 lb						
CSBS4	1/4" - 3/8"	3,000 lb	2,200 lb						
	3/8" - 3/4"	3,000 lb	2,765 lb						
CSBS5	3/4" - 1 1/4"	3,000 lb	2,500 lb						

FM Loads									
	Horizontal Capacity per Installation Angle from Vertical								
Part Number	Perpendicular to Structure			Parallel to Structure					
	30° - 44°	45° - 59°	60° - 74°	75° - 90°	30° - 44°	45° - 59°	60° - 74°	75° - 90°	
CSBS3xx	1,180 lb	2,210 lb	2,830 lb	2,940 lb	820 lb	1,380 lb	2,080 lb	3,010 lb	
CSBS4xx	1,180 lb	2,210 lb	2,830 lb	2,940 lb	820 lb	1,380 lb	2,080 lb	3,010 lb	
CSBS5xx	1,220 lb	2,140 lb	2,580 lb	2,870 lb	1,100 lb	1,820 lb	2,190 lb	2,680 lb	

FM is a registered certification mark of FM Approvals LLC, LTD. NFPA is a registered trademark of National Fire Protection Association, Inc. UL, UR, cUL, cUR, and cURus are registered certification marks of UL LLC.

WARNING

New tproducts shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

