

Noninsulated Flexible Duct

Conducto Flexible

Overview

Descripción y Aplicaciones

Flexible aluminum foil duct can be used in a variety of general purpose exhaust and ventilation applications. Made of aluminum foil laminate structured with steel wire. Highly flexible and compressible.

Conducto flexible formado con hojas de aluminio, para la utilización en varias aplicaciones generales de ventilación. Hecho de estructura laminada de papel de aluminio con alambre de acero. Altamente flexible y compresible.



Features - FLEX AP

Características - FLEX AP

Model	Diameter	Length
<i>FLEX 100 AP</i>	<i>100 / 4"</i>	<i>32 ft / 10 m</i>
<i>FLEX 125 AP</i>	<i>125 / 5"</i>	<i>32 ft / 10 m</i>
<i>FLEX 150 AP</i>	<i>150 / 6"</i>	<i>32 ft / 10 m</i>
<i>FLEX 200 AP</i>	<i>200 / 8"</i>	<i>32 ft / 10 m</i>

- Available in 4", 5", 6" and 8"
- Rated Positive Pressure 10" W.C.
- Rated Negative Pressure 1" W.C.
- Velocity 5000 FPM
- Temperature Range -10°F to 160°F (Intermittent) / -10°F to 140°F (Continuous)
- Made of metalized polyester Film
- Support point over 1,5 Feet

Features - FLEX APA

Características - FLEX APA



Model	Diameter	Length
<i>FLEX 100 APA</i>	<i>100 / 4"</i>	<i>32 ft / 10 m</i>
<i>FLEX 125 APA</i>	<i>125 / 5"</i>	<i>32 ft / 10 m</i>
<i>FLEX 150 APA</i>	<i>150 / 6"</i>	<i>32 ft / 10 m</i>
<i>FLEX 200 APA</i>	<i>200 / 8"</i>	<i>32 ft / 10 m</i>

- Available in 4", 5", 6" and 8"
- Rated Positive Pressure 10" W.C.
- Rated Negative Pressure 1/2" W.C.
- Velocity 5500 FPM
- Temperature Range -15°F to 180°F (Intermittent) / -15°F to 160°F (Continuous)
- Made of a heavy duty aluminum foil laminate
- Support point over 2 Feet