



**We Know Water.**

## UNIVERSAL BI-LEVEL MODULAR WITH BUILT IN HANDS-FREE BOTTLE FILLER

- **M8CREBF**
- **M12CREBF**
- **MCREBF**

### Suggested Specification

Model M8CREBF shall deliver 8.0 gph of 50°F degree water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model M12CREBF shall deliver 12.0 gph of 50°F degree water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model MCREBF is a non-refrigerated unit. Shall include two vandal-resistant push buttons to activate the flow of water and a low flow one piece bubbler with flexible guard. The fountains shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Key Aqua Pointe™ bottle filler components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Cabinet finish shall be brushed stainless steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



	M8CREBF	M12CREBF	MCREBF
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Built-in 100 micron strainer stops particles before they enter the waterway</li> <li>• Two vandal-resistant antimicrobial push buttons</li> <li>• Hands-free bottle filler with 20 second shut off, integrated bottle counter and filter monitor</li> <li>• Waterways are Lead-Free in materials &amp; construction</li> <li>• Flexible bubbler guard</li> <li>• Brushed stainless steel finish</li> <li>• Universal design: high right or high left</li> <li>• High efficiency cooling system</li> <li>• Built in panel locks for easy access to chiller and filtration</li> </ul>		
<b>Power:</b>	115 Volts, 60 Hz		
<b>Activation By:</b>	Contactless Sensor on Bottle Filler and Manual Activation on Fountains.		
<b>Mounting Type:</b>	In Wall		
<b>Chilling Option:</b>	8.0 gph	12.0 gph	Non-Refrigerated
<b>Installation Location:</b>	Indoor		

### Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions
- Frame allows for universal installation
- Recessed mounting frame included, but water supply and drain required

### Finishes

- Standard cabinet finish: Stainless steel

### Options

- One piece chrome plated brass bubbler (036700-001)

### Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

### Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\*Industry standard rating condition 80°F inlet water temperature

Specifications subject to change without notice

# OASIS® UNIVERSAL BI-LEVEL MODULAR WITH BUILT IN HANDS-FREE BOTTLE FILLER

