



We Know Water.

UNIVERSAL BARRIER-FREE VERSACOOLER® II WITH HANDS-FREE VERSAFILLER

- **PG8EBFSL**
- **PGEBFSL**

Suggested Specification

Model PG8EBFSL shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGEBFSL is a non-refrigerated drinking fountain and delivers ambient water. Both shall include the VersaFiller sports bottle filler with hands-free activation; fountains shall have four push pads to activate the manual flow of water for the cooler. Hands-free VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be brushed stainless steel or greystone on galvanized steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



	PG8EBFSL	PGEBFSL
Features:	<ul style="list-style-type: none"> • Waterways are Lead-Free in materials & construction • Flexible one-piece water saver bubbler guard infused with silver based antimicrobial additive • Stainless steel top and heavy duty galvanized steel frame • High efficiency cooling system and refrigerant R-134a • Four push pads per fountain • External stream height adjustment on lower unit • Hands-free VersaFiller • Built in filter monitor and bottle counter 	
Filtration:	Option to add VersaFilter Filtration System	
Power:	115 Volts, 60 Hz	
Activation By:	Contactless Sensor on Bottle Filler and Manual Activation on Fountains	
Mounting Type:	Wall Mounted	
Chilling Option:	8.0 gph	Non-Refrigerated
Installation Location:	Indoor	

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation.

Finishes

- Standard cabinet finish: Greystone powder coated paint on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

Options

- One piece chrome plated brass bubbler (036700-001)
- VersaFilter

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



*Industry standard rating condition 80°F inlet water temperature

Specifications subject to change without notice

UNIVERSAL BARRIER-FREE VERSACOOLER® II WITH HANDS-FREE VERSAFILLER

OASIS® VERSACOOLER® II MODELS with VersFiller®
 PGEFBSL, PGVEFBSL, PGEFBSLTM, PG8EFBSL, PGV8EFBSL, PG8EFBSLTM,
 PGFEBFBSL, PGFEBFBSLTM, PGV8EFBSL, PGF8EFBSL, PGF8EFBSLTM, PGV8EFBSL

