

Fig. 186 (Formerly Afcon Fig. 510)

Two Hole Pipe Strap

Size Range: 3/4" through 3"

Finish: Pre-Galvanized Carbon Steel per ASTM A653

Service: Hanger for CPVC, steel, & copper pipe in the horizontal position on the bottom and side of structural wood beams, composite beams and Steel 20 Ga. (min.) (Fig. A, C respectively). Can be used as a restrainer when installed on top of structural wood beams (Fig. B), for limiting pipe movement due to thrust loads during sprinkler system start-up. It can also be used as a guide to limit movement for pipe in the vertical position. When used on composite wood beams, web thickness must be $^3/_8$ " or greater.

Approvals: cULus Listed

Installation:


- Snap hanger over pipe.
- Secure hanger to mounting surface with screws provided.
- Do not make adjustments to hanger mounting flanges that result in clamping the pipe to the mounting surface. Pipe must be allowed to move freely through hanger.
- Steel applications require two (2) #14 x 1" hex washer head self-drilling TEK screws. Not Supplied. Part Number STD-0090.


Features:

- Beveled edge design helps protect the CPVC pipe from any rough surface.
- Easily attaches to wood structure with #10 x 1" hex washer head self threading screw supplied with product. No pre-drilling required.
- Retaining dimples hold the strap onto the pipe for ease of installation. (Not shown)

Ordering: Specify pipe size, figure number, and description.










Fig. A Fig. B Fig. C

FIG. 186: DIMENSIONS (IN) • WEIGHT (LBS)						
Pipe Size	A	В	øC	E	F	Approx. Weight/100 (lbs)
3/4	1	213/16	1/4	11/8	11/8	5
1	11/4	31/4			11/2	6
11/4	1 5⁄16	33//8			111/16	7
1½	1%16	37//8			21/8	8
2	113/16	4 ⁵ / ₁₆			29/16	9
21/2	21/4	53//8		13/16	27/8	14
3	25/8	65/16			31/2	17

PROJECT INFORMATION	APPROVAL STAMP
Project:	☐ Approved
Address:	Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	