





No recharging or power stealing. 5-year Pro install warranty.

5-YEAR PRO INSTALL WARRANTY

Get an extra 2 years of warranty when you professionally purchase and install your ecobee3 lite.



Part Numbers:	Description	Std Pack Qty
EB-STAT3LTBX-01	ecobee3 lite Pro Builder Pack	10

Here's why pros love us.

NO POWER-STEALING OR RECHARGING

COMPATIBLE WITH MOST

Works with gas, oil, electric, and dual-fuel systems.

Supports conventional (2H/2C) and heat pump (4H/2C) systems; humidifier, dehumidifier, ventilator, HRV, or ERV accessories. For full details, visit ecobee.com/compatibility.

EASY TO INSTALL

Here's why consumers love us.

CONTROL FROM ANYWHERE

Customers can control their ecobee from anywhere with an iOS or Android device.

PAYS FOR ITSELF IN UNDER 2 YEARS*


Keeps energy use low when no one is home, making way for savings where it counts. *Compared to a 72°F hold.

AT YOUR CONVENIENCE

Monitors heating and cooling systems and alerts customers if it senses something is wrong.

HELPS MANAGE HOT OR COLD SPOTS

Pairs with Room Sensors[™] to help with hot or cold spots throughout the home. Room Sensors measure temperature to deliver comfort to the rooms that matter most. Sold separately.



SUPPORT HOURS

Available 8am-12am (Mon-Fri) and 9am-9pm (Sat-Sun). 1.866.518.6740 | support@ecobee.com







TECH SPECS

COMPATIBILITY

Conventional (2H/2C)—Gas, oil, electric. Boiler (2-stage-heating).

Air-Cooled & Geo-Thermal Heat pumps (2 stage heat pump + 2 stage aux heat/2 cool) (4H/2C).

Dual-Fuel support.

WIRE TERMINALS

RC	O/B	W1
G	RH	W2
Y1	С	PEK
140		

Y2

POWERING METHOD

Wired 24VAC through terminals C or Rc.

POWER CONSUMPTION

Less than 3.5VA

CONNECTIVITY AND SECURITY

Wi-Fi, IEEE 802.11 b/g/n @ 2.4 GHz Wi-Fi Protected Access (WPA/WPA2) Wired Equivalent Privacy (WEP) DHCP (dynamic) or static IP addressing Transport Layer Security (TLS) 915MHz

BANDWIDTH

15-20 MB/month

SUSTAINABILITY

Mercury free Arsenic free PVC free ROHS compliant

THERMOSTAT SENSORS

Temperature Proximity Humidity

ROOM SENSOR

Temperature Motion

TEMPERATURE RANGE

Temperature: 7° to 33°C (45° to 92°F)
Display: 5° to 37°C (40° to 100°F)
Sensitivity: +/- 0.5°C (+/- 1°F)
Operating: 0° to 55°C (32° to 130°F)

HUMIDITY RANGE

Display: 20% to 90% RH Sensitivity: +/- 5% RH

Operating: 5% to 95% RH (non condensing)

STORAGE

-35° to 45°C (-31° to 113°F) 5% to 95% RH (non condensing)

LANGUAGES

English

DISPLAY

3.5" full-color LCD touch screen 320 x 480 pixel display

HOMEKIT-ENABLED

HomeKit requires an iPhone, iPad, or iPod touch with iOS 9 or later. Controlling HomeKit-enabled accessories away from home requires an Apple TV with tvOS 9.0 or later and an iPhone, iPad, or iPod touch with iOS 9 or later.

WARRANTY

5-year warranty (PRO Install only)

WHAT'S IN THE BOX

ecobee3 lite thermostat

Backplate Screws

Dry wall plugs

PRODUCT DIMENSIONS

Thermostat Length: 102.88 mm Width: 102.88 mm Depth: 21.4 mm











Contact ecobee for full integration list.

HVAC-E3LPROSELLSHT-01