

PFINHC Series

Standard No-Hub Coupling



Product Features

- The PROFLO Standard No-Hub Coupling conforms to CISPI 310 and ASTM C1277
- Band and housing type 301 AISI stainless steel
- Screw type 300 Series AISI stainless steel 5/16" hex head
- Shield type 301 AISI corrugated stainless steel, thickness of 0.007"
- Gasket made from an elastomeric compound that meets ASTM C564

Codes and Certifications



PFINHCJ

Available Sizes

Size	SKU	Install Torque Inch Pounds	No. of Clamps per Coupling
1-1/2"	PFINHCJ	60	2
2"	PFINHCK	60	2
3"	PFINHCM	60	2
4"	PFINHCP	60	2
5"	PFINHCS	60	4
6"	PFINHCU	60	4
8"	PFINHCX	60	4
10"	PFINHC10	60	4

For detailed warranty information, visit ferguson.com/PROFLO-1-year-warranty.

PFINHCHD Series

Heavy-Duty No-Hub Coupling



Product Features

- The PROFLO Heavy-Duty No-Hub Coupling conforms to CISPI 310 and ASTM C1540
- Clamp type 304 AISI stainless steel
- Screw type 300 Series AISI stainless steel 3/8" hex head/shoulder
- Shield type 304 AISI corrugated stainless steel, thickness of 0.008"
- Gasket made from an elastomeric compound that meets ASTM C564

Codes and Certifications



PFINHCHDJ / PFINHCHDP

Available Sizes

Size	SKU	Install Torque Inch Pounds	No. of Clamps per Coupling
1-1/2"	PFINHCHDJ	80	4
2"	PFINHCHDK	80	4
3"	PFINHCHDM	80	4
4"	PFINHCHDP	80	4
5"	PFINHCHDS	80	6
6"	PFINHCHDU	80	6
8"	PFINHCHDX	80	6
10"	PFINHCHD10	80	6

For detailed warranty information, visit [ferguson.com/PROFLO-1-year-warranty](https://www.ferguson.com/PROFLO-1-year-warranty).