

## PRODUCT SPECIFICATIONS

Outdoor ezH2O® Bottle Filling Station Wall Mount with Bi-Level Fountain Non-Filtered Non-Refrigerated. Features shall include Heavy Duty Vandal Resistant, Laminar Flow, 300 Series Stainless. Furnished with Vandal Resistant bubbler. Mechanical Button activation. Product shall be Wall Mount (On Wall), for Outdoor applications, serving 3 station(s).

|                                 |                                                                 |
|---------------------------------|-----------------------------------------------------------------|
| <b>Special Features:</b>        | Heavy Duty Vandal Resistant, Laminar Flow, 300 Series Stainless |
| <b>Finish:</b>                  | Black (BK), Blue (BLU), Evergreen (EVG), Gray (GRY)             |
| <b>Power:</b>                   | No Electrical Required                                          |
| <b>Bubbler Style:</b>           | Vandal Resistant                                                |
| <b>Activation by:</b>           | Mechanical Button                                               |
| <b>Mounting Type:</b>           | Wall Mount (On Wall)                                            |
| <b>Chilling Capacity:</b>       | Non-refrigerated                                                |
| <b>Dimensions (L x W x H):</b>  | 21-1/4" x 32-7/8" x 38-7/16"                                    |
| <b>Approx. Shipping Weight:</b> | 203 lbs.                                                        |
| <b>Installation Location**:</b> | Outdoor                                                         |
| <b>No. of Stations Served:</b>  | 3                                                               |

\*\*When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.

**Special Note: Wall Mounted Bottle Filler Station (1), Bubbler Stations (1 Upper, 1 Lower), Choose from 4 color options**

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Laminar flow provides clean fill with minimal splash.



### Ships in one box.

A Century of Tradition and Quality. For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.

### PRODUCT COMPLIANCE

ADA & ICC A117.1

ASME A112.19.3/CSA B45.4

GreenSpec®

NSF REG4



Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

[Installation Instructions \(PDF\) - 1000004377](#)

**Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.**

[Warranty \(PDF\)](#)

PART: \_\_\_\_\_ QTY: \_\_\_\_\_

PROJECT: \_\_\_\_\_

CONTACT: \_\_\_\_\_

DATE: \_\_\_\_\_

NOTES: \_\_\_\_\_

APPROVAL: \_\_\_\_\_

*In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit [elkay.com](http://elkay.com) for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.*

**MOUNTING INSTRUCTIONS and  
PLUMBING CONNECTIONS**

Refer to diagrams for plumbing rough-in. This fountain is to be mounted on a smooth, flat finished wall surface with adequate support.

**Note:** Wall mounting structure must be capable of supporting 300lb. load minimum on fountain. To secure unit, use 3/8" minimum fasteners (not provided). Water service line and waste line are to be assembled as required. Final check for leaks and correct functions of fountain should be made. (For details see the installation instructions.)

**Installation requires trap to be installed in wall. A service supply stop must be installed at the fountain inlet line. Trap and service stop not included.**


**Caution - Fountain must be securely bolted to wall.**

**Note:** For wall support required locations see installation instructions provided with fountain.


**OPERATING PRESSURES:**

Supply water 20 - 105 psi maximum


**TOP VIEW**



**OPERATION OF QUICK CONNECT FITTINGS**




PUSHING TUBE IN BEFORE  
PULLING IT OUT HELPS TO  
RELEASE TUBE



**BACK VIEW**

**SIDE & FRONT VIEWS**



\* ADA Requirement

A = 3/8" O.D. UNPLATED COPPER TUBE CONNECT - SHUT OFF VALVE BY OTHERS

B = REMOVABLE BOTTOM COVER

C = IN-LINE STRAINER

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit [elkay.com](http://elkay.com) for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.