

Rev. 4-20 Shaded area indicates changes



**H-10887**

**Brass meter idler**  
Has same end-to-end and thread dimensions as meter. Used to continue service during meter repairs

|                   |        |             |      |         |
|-------------------|--------|-------------|------|---------|
| Catalog size      | 5/8"   | 5/8" x 3/4" | 3/4" | 1"      |
| Cover size        | 5/8"   | 5/8" x 3/4" | 3/4" | 1"      |
| Length            | 7-1/2" | 7-1/2"      | 9"   | 10-3/4" |
| Meter thread size | 3/4"   | 1"          | 1"   | 1-1/4"  |



**H-14338**

**Brass locking device (padlock and valve not included)**  
For use on Mueller® MARK II ORISEAL® Meter Valves - cannot be used on valves having angle lever handles.

|              |      |    |
|--------------|------|----|
| Catalog size | 3/4" | 1" |
|--------------|------|----|



**Water meter increaser**  
Used on threaded ends of 5/8" meter to increase threads to 5/8 x 3/4 or 3/4 meter size (1" thread)  
**H-10888**: for plain nuts  
**H-10888-99002**: for saddle nuts

**H-10888N H-10888N-02**

|              |             |             |
|--------------|-------------|-------------|
| Catalog size | 5/8" x 3/4" | 5/8" x 3/4" |
| Meter size   | 5/8"        | 5/8"        |
| Length       | 11/16"      | 1"          |



**H-11091 H-11092**

**Lock wing sealing device**  
This device is used to detect unauthorized use of valve or stop. Used with lock wings drilled 3/8" or 1/2". The H-11090 is made up of a collar and set screw (H-11091) and a pin (H-11092). The pin is available in 3/8" or 1/2" sizes and the collar with set screw is used on both sizes.




**H-11090**



**Meter bushing with rubber washer**  
Used on threaded ends of 5/8 x 3/4 or 3/4 meters to adapt to 1" meter thread size (1-1/4")  
**H-10889**: for saddle nuts  
**H-10889-99000**: for plain nuts

**H-10889N H-10889N-00**

|              |                   |                   |
|--------------|-------------------|-------------------|
| Catalog size | 3/4" x 1"         | 3/4" x 1"         |
| Meter size   | 5/8" x 3/4", 3/4" | 5/8" x 3/4", 3/4" |
| Length       | 1-1/4"            | 15-16"            |



**H-10879N**

**Meter bushing with rubber washer (complete for both ends)**  
Used on threaded ends of 5/8x3/4 meter to adapt to 1" meter thread size (1-1/4") and standard length.

|              |             |           |                  |           |                    |             |         |             |
|--------------|-------------|-----------|------------------|-----------|--------------------|-------------|---------|-------------|
| Catalog size | 5/8" x 3/4" | 5/8" x 1" | 5/8" x 3/4" x 1" | 3/4" x 1" | 5/8" x 3/4" x 3/4" | 1" x 1 1/2" | 1" x 2" | 1 1/2" x 2" |
| Meter size   | 5/8"        | 5/8"      | 5/8" x 3/4"      | 3/4"      | 5/8" x 3/4"        | 1"          | 1"      | 1 1/2"      |
| Length       | 1.019"      | 2.062"    | 2.062"           | 1.13"     | 1.019"             | 1"          | 3"      | 1.875"      |



**H-10893**

**Meter coupling washer**  
**H-10893**: Fiber washer

|              |      |                   |    |        |           |       |
|--------------|------|-------------------|----|--------|-----------|-------|
| Catalog size | 5/8" | 3/4"              | 1" | 1-1/4" | 1-1/2" ** | 2" ** |
| Meter size   | 5/8" | 5/8" x 3/4", 3/4" | 1" | 1-1/4" | 1-1/2"    | 2"    |



**H-10895**

**Meter coupling washer**  
**H-10895**: Rubber washer

|              |      |                   |    |        |           |       |
|--------------|------|-------------------|----|--------|-----------|-------|
| Catalog size | 5/8" | 3/4"              | 1" | 1-1/4" | 1-1/2" ** | 2" ** |
| Meter size   | 5/8" | 5/8" x 3/4", 3/4" | 1" | 1-1/4" | 1-1/2"    | 2"    |

\*\* Flange gasket for 1-1/2" and 2" sizes.

\*\* Flange gasket for 1-1/2" and 2" sizes.

8E-COUPPLINGS/MISC.

April 28, 2017

Subject: Mueller Co. Service Brass

To Whom It May Concern:

This will certify that Mueller Co. service brass, which includes corporation stops, curb stops, service fittings, meter valves, copper meter yokes and end connections, are manufactured and tested in accordance with the latest revision of AWWA C800 standard and are certified to NSF 61.

Components that come in contact with potable water comply with the latest requirements of the U.S. Federal Safe Drinking Water Act that was enacted on January 4, 2014.

Sincerely,



Larry Aulich  
Senior Product Manager  
Mueller Company