

BEFORE YOU BEGIN

We recommend consulting a professional if you are unfamiliar with installing bathroom fixtures and plumbing. Signature Hardware accepts no liability for any damage to the floor, walls, plumbing, or personal injury during installation.

Observe all local plumbing and building codes.

Unpack and inspect the tub for damage. If any damage is found, contact our Customer Relations team at 1-866-855-2284.

GETTING STARTED

- Ensure that you have gathered all of the required materials that are needed for the installation.
- Ensure that your bathroom floor is adequately supported, and the finished floor is level.
- Keep the plumbing connections around the tub easily accessible for any future maintenance that may be necessary.

PLANNING

Use the tub's PDF specification sheet as a reference when planning your layout. The specification sheet can be found and downloaded from the product page on our website.

Because the tub specification measurements are approximate and slight variations may occur, we highly recommend performing any rough-in procedures with the faucet on site. For rough-in information, go to the appropriate drain installation section.

TOOLS AND MATERIALS:







Marker

Tape Measure

Straight Edge







Metal Blade Hacksaw

Thread Sealant

Plumber's Tape







Adjustable Wrench

Neutral Cure Silicone Sealant

PVC Primer and Cement




Damp Cloth





INSTALLATION


1. Set the tub in the desired installation location and mark the drain hole location on the floor.









2. Move the tub away from the installation location so that the plumbing can be installed. The drain pipe should extend approximately 6" above the finished floor.



3. Trim the $1-\frac{1}{2}$ " PVC drain pipe extending from the floor to the appropriate length. This can be determined by attaching the drain to the tub and measuring the distance from the finished floor to the center of the fitting socket.




4. Attach the drain's hub adapter to the PVC pipe with PVC primer and cement. Place the rubber washer on the rim of the adapter.




customer service: 1.866.855.2284 signature hardware.com




5. Carefully set the tub into position over the drain.




6. Apply 100% neutral cure silicone sealant to the underside of the drain flange and thread it through the tub and into the drain pipe. Apply thread sealant or plumber's tape to the threaded connection to ensure a water-tight seal. Tighten by hand. Wipe away any excess sealant using a damp cloth.






7. Fill the tub with water to check for any leaks from the connections. Verify that the drain is working properly.



8. Finish your installation by running a bead of neutral cure silicone sealant around the base of the tub where it meets the floor. Wipe away any excess sealant with a damp cloth.





CLEANING AND MAINTENANCE

We recommend that you regularly clean your natural stone tub with a mild dish detergent or stone cleaner. After each use, wipe dry with a soft cloth. Do not allow mineral deposits such as iron, salt, lime, or soap to build up. Refrain from using acidic household cleaners, wipes with harsh chemicals, or abrasives, as these can damage the stone. To remove stains, use a standard stone and tile stain remover. For more difficult stains, apply a liquid poultice cleaning product directly to the stain.

Because stone is porous, it is important to protect against harmful substances. Seal the stone using a heavy-duty stone sealer. To retain your tub's natural shine, reseal once or twice per year.

One of the distinctive characteristics of natural stone are voids, or gaps, in the surface of the stone. To fill any unwanted voids, use a stone filler. Stone filler products are available in various colors to match the color of your stone.