

Location:

Project: Fixture Type:

Contact:

**LED Flush Mount** 

Ceiling mounted • Damp location listed PROGRESS LED



## P350113-009-30

Images:

The Fresnel LED flush mount features a nautical-inspired Fresnel glass lens, with industrial roots in form and function. Ideal for Farmhouse, Coastal and Industrial interiors. Complimented by a Brushed Nickel finish.

#### **Specifications:**

**Description:** 

- Brushed Nickel (-009) (plated)
- Steel construction
- Etched Fresnel Glass Round
- LED Module is replaceable (part # 93074039)
- Fresnel LED flush mount
- Features an antique-inspired Fresnel glass lens, industrial roots in form and function
- 1-light 17-watt LED flush mount fixture
- Suitable for ceiling mount applications
- Measures 12 3/4" diameter x 4 1/2" H
- 937 lumens, 53.9 lumens per watt [per LM-79 (delivered)]
- Warm white 3000K lighting color, 90+CRI
- Ideal for low ceilings or small foyer spaces that showcase Farmhouse, Coastal and Industrial interiors
- · Close-to-ceiling lights are natural choices for closets, hallways, and small rooms
- Semi-flush fixtures are good choices to brighten an entire room ideal for ambient or general illumination
- Replaceable light engine
- Damp location listed.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR<sup>®</sup> qualified
- Meets California Title 24 JA8-2016

### Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1276/73 (LM-82)
Lumens/LPW (Delivered)	937/53.9 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Warranty	5 year limited warranty
Labels	cCSAus Damp location listed
	ENERGY STAR <sup>®</sup> qualified
	Meets California Title 24 JA8-2016



#### **Dimensions:**

Diameter: 12-3/4" Height: 4-1/2"

Glass Width: 10-1/16" Height: 1"



# LED Flush Mount

Ceiling mounted • Damp location listed PROGRESS LED



#### **Dimming Notes:**

P350113 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

#### **Dimming Controls**

Lutron Diva DVELV-300P	
Lutron Nova T NTELV-300	
Lutron Caseta	
Lutron Ariadni AY-600P	
Leviton Illumatech IPI06-1LZ	
Lutron Lumea LG-603PG	
Leviton SureSlide 6672	
Leviton SureSlide 6674	
Lutron Ariadni AYCL-153P	
Lutron Skylark Contour CTCL-153P	
Lutron Diva DVCL-153P	
Pass & Seymour Harmony DCL453PTCCCV6	
Lutron Toggler TGCL-153P	
Lutron Maestro MACL-153M	
Lutron Ariadni AYLV-600P	
Lutron Maestro MA-600	
Lutron NOVA T NTLV-600	
lutron Maestro MAELV-600	
Lutron spacer/system SPSELV-600	
Lutron Renoir II AWRMG-EAW	

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.