

The new Miller Titan™ II line of lanyards is economical and features Hi-Viz color for increased worksite safety and quick availability with in-stock items. All connectors are rated at 3,600-lb. gate-strength.



T5112-Z7/6FTAF



T5111SS-Z7/6FTAF



T6111-Z7/6FTAF



T6111SS-Z7/6FTAF



T9111W-Z7/6FTAF



T6111TB-Z7/6FTAF

Limitless Possibilities. Ask the Expert.

www.millerfallprotection.com
Technical Service: 800.873.5242

Honeywell Industrial Safety

900 Douglas Pike
Smithfield, RI 02917

U.S. Tel: 800.430.5490
Fax: 800.322.1330
CANADA Tel: 888.212.7233
Fax: 888.667.8477

www.honeywell.com

SKU	Number of Legs	Harness Connection	Anchorage Connection	Standard Length*
TITAN™ II TUBULAR SHOCK-ABSORBING LANYARDS				
T5122-Z7/6FTAF	Two	Locking snap hook	Large locking rebar hooks	6-ft. (1.8 m)
T5111-Z7/6FTAF	One	Locking snap hook	Locking snap hook	6-ft. (1.8 m)
T5121-Z7/6FTAF	Two	Locking snap hook	Locking snap hooks	6-ft. (1.8 m)
T5112-Z7/6FTAF	One	Locking snap hook	Large locking rebar hook	6-ft. (1.8 m)

*Available in lengths from 4-ft. (1.2 m) to 10-ft. (3 m). Locking Snap Hook – 3/4-in. (19 mm) gate opening. Large locking rebar hook – 2-1/2-in. (64 mm) gate opening.

TITAN™ II STRETCH TUBULAR BUILT-IN SHOCK-ABSORBING LANYARDS				
T5122SS-Z7/6FTAF	Two	Locking snap hook	Large locking rebar hooks	Contracts 6-ft. (1.8 m) to 4-ft. (1.2 m)
T5111SS-Z7/6FTAF	One	Locking snap hook	Locking snap hook	Contracts 6-ft. (1.8 m) to 4-ft. (1.2 m)
T5121SS-Z7/6FTAF	Two	Locking snap hook	Locking snap hooks	Contracts 6-ft. (1.8 m) to 4-ft. (1.2 m)
T5112SS-Z7/6FTAF	One	Locking snap hook	Large locking rebar hook	Contracts 6-ft. (1.8 m) to 4-ft. (1.2 m)

*Available in lengths from 4-ft. (1.2 m) to 10-ft. (3 m). Locking Snap Hook – 3/4-in. (19 mm) gate opening. Large locking rebar hook – 2-1/2-in. (64 mm) gate opening.

TITAN™ II PACK-TYPE SHOCK-ABSORBING LANYARDS				
T6122-Z7/6FTAF	Two	Locking snap hook	Large locking rebar hooks	6-ft. (1.8 m)
T6111-Z7/6FTAF	One	Locking snap hook	Locking snap hook	6-ft. (1.8 m)
T6121-Z7/6FTAF	Two	Locking snap hook	Locking snap hooks	6-ft. (1.8 m)
T6112-Z7/6FTAF	One	Locking snap hook	Large locking rebar hook	6-ft. (1.8 m)

*Available in lengths from 3-ft. (0.91 m) to 10-ft. (3 m). Locking Snap Hook – 3/4-in. (19 mm) gate opening. Large locking rebar hook – 2-1/2-in. (64 mm) gate opening.

TITAN™ II STRETCH PACK-TYPE SHOCK ABSORBING LANYARDS				
T6122SS-Z7/6FTAF	Two	Locking snap hook	Large locking rebar hooks	Contracts 6-ft. (1.8 m) to 4-ft. (1.2 m)
T6111SS-Z7/6FTAF	One	Locking snap hook	Locking snap hook	Contracts 6-ft. (1.8 m) to 4-ft. (1.2 m)
T6121SS-Z7/6FTAF	Two	Locking snap hook	Locking snap hooks	Contracts 6-ft. (1.8 m) to 4-ft. (1.2 m)
T6112SS-Z7/6FTAF	One	Locking snap hook	Large locking rebar hook	Contracts 6-ft. (1.8 m) to 4-ft. (1.2 m)

*Available in lengths from 3-ft. (0.91 m) to 10-ft. (3 m). Locking Snap Hook – 3/4-in. (19 mm) gate opening. Large locking rebar hook – 2-1/2-in. (64 mm) gate opening.

TITAN™ II POSITIONING LANYARDS				
T9111W-Z7/6FTAF	One	Locking snap hook	Locking snap hook	6-ft. (1.8 m)
T9112W-Z7/6FTAF	One	Locking snap hook	Large locking rebar hook	6-ft. (1.8 m)

*Available in lengths from 2-ft. (.6 m) to 10-ft. (3 m). Locking Snap Hook – 3/4-in. (19 mm) gate opening. Large locking rebar hook – 2-1/2-in. (64 mm) gate opening.

TITAN™ II TIE-BACK LANYARDS with Pack-Type Shock Absorber				
T6121TB-Z7/6FTAF	Two	Locking snap hook	Auto-lock carabiners; Forged sliding D-rings	6-ft. (1.8 m)
T6111TB-Z7/6FTAF	One	Locking snap hook	Auto-lock carabiners; Forged sliding D-rings	6-ft. (1.8 m)

*Available in lengths from 3-ft. (0.91 m) to 10-ft. (3 m). Locking Snap Hook – 3/4-in. (19 mm) gate opening. Large locking rebar hook – 2-1/2-in. (64 mm) gate opening.

All connectors include 3,600-lb. gate-strength. All Miller brand fall protection products meet applicable OSHA, ANSI and CSA requirements. For CSA Z259 models, when ordering add a "C" at the end of the model number, ie.: T5122-Z7/6FTAFC, with the exception of T9111W-Z7/6FTAF, T9112W-Z7/6FTAF in which the SKU does not change to meet CSA.

WARNING! This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.

LMBT | 3/16
© 2016 Honeywell International Inc.

Honeywell