

## 83709SB7

9' DuraTech® Cable SRL with Steel Swivel Snap Hook, Includes Steel Anchorage Carabiner

### Features :

- Compact size is simple to install and relocate as worksite changes require
- 3/16" galvanized steel cable lifeline with load-indicating swivel snap hook.
- Glass-filled nylon housing contributes unmatched impact resistance
- Integrated aluminum alloy swivel-eye helps to prevent lifeline twisting for smooth operation
- Includes alloy steel anchorage carabiner
- Complies with ANSI Z359.14-2014



| Material Specifications    |   |
|----------------------------|---|
| <b>Cable</b>               | 3/16" galvanized steel; 3,400 lb min. static strength                         |
| <b>Lifeline Connector</b>  | Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength |
| <b>Anchorage Connector</b> | Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength |

| Performance Specifications  |                    |
|-----------------------------|--------------------|
| <b>Static Strength</b>      | 3,000 lb min.      |
| <b>ANSI SRL Class</b>       | Class B            |
| <b>Avg. Arrest Force</b>    | 900 lb             |
| <b>Max. Arrest Force</b>    | 1,800 lb           |
| <b>Max. Arrest Distance</b> | 54"                |
| <b>ANSI User Capacity</b>   | 130 to 310 lb max. |
| <b>OSHA User Capacity</b>   | 130 to 310 lb max. |

| Compliant With: |                      |
|-----------------|----------------------|
| <b>OSHA</b>     | 1926.502 and 1910.66 |
| <b>ANSI</b>     | Z359.14-2014         |
| <b>CSA</b>      | Z259.2.2-2017        |

### Sizes & Part Numbers

|                              |                              |  |
|------------------------------|------------------------------|--|
| 83709SB7<br>(ANSI Compliant) | C83709SB7<br>(CSA Compliant) |  |
|------------------------------|------------------------------|--|