



BRIDGE FAUCET

INSTALLATION INSTRUCTIONS

Before installing, read entire Bridge Faucet Installation Instructions. Observe all local building and safety codes.

For the following installation instructions for your new Bridge Faucet it is assumed that any old fixtures have been removed and any repairs or modifications to the water supply have been completed.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-855-715-1800. If you need assistance or have questions while installing your Bridge Faucet, contact Customer Service.

We recommend consulting a professional if you are unfamiliar with installing kitchen fixtures. Signature Hardware accepts no liability for any damage to the floor, walls, plumbing or for personal injury during installation.

Turn off the water supply at the sink where the new faucet is being installed.

TOOLS AND MATERIALS:

Adjustable Wrench

Teflon Pipe Tape

Basin Wrench

INSTALLATION

1. Attach the bottom of the handle assembly to the faucet if not already attached, making sure to include any rubber washers or sealing gaskets provided. Remove the lock nuts from the bottom of the threaded handle shanks and insert through the mounting holes.
2. Hand-tighten washers (if included) and hex nuts from underneath the sink to secure.
3. Check to make sure the faucet is properly aligned and adjust as needed. When the faucet is in the proper position, finish tightening the hex nuts with your adjustable wrench.
4. If your faucet features a side spray, install by inserting the sprayer housing, and rubber sealing gasket through the mounting hole. Secure by tightening the lock nut from underneath the sink. If your faucet does not have a side spray move on to step 6.
5. Attach the spray nozzle to the spray hose if not already attached and insert through the sprayer housing. Attach the hose to the spray hose outlet on the faucet.

Tip: Before you connect the spray hose to the faucet, make sure that it is in a position that will allow you to pull it out easily without getting caught on any other fixtures under the sink.

6. Hand tighten to attach the hot and cold water feed tubes to the water inlets; hot water is always on the left and cold water is always on the right. Give a ¼ turn with pliers or wrench, but don't over tighten. Curve tubes as necessary to ensure there are no kinks or knots.

Tip: Place plumber's tape on hoses and pipes before you attach supply lines to ensure leak-free connections.

7. After all connections have been made, turn on the water supply, check to make sure that all connections are tight (no water should be leaking) and that the hot and cold supplies are working correctly. Turn the faucet on and allow the water to flow through the spout for approximately 60 seconds. Divert the water to the spray hose and allow the water to flow through the hose for approximately 60 seconds.