

TOSCA THERMOSTATIC SHOWER SYSTEM WITH RAINFALL SHOWER AND HAND SHOWER

SKU: 925942

Code: SH379999, SH380000, SH380001



FEATURES

Material: Brass
Shower Head Swivel: Yes
Shower Head Spray: Rainfall
Shower Head Flow Rate: 2.0 gpm (7.6 L/min) @ 80 psi
Hand Shower Spray: Full
Hand Shower Flow Rate: 2.0 gpm (7.6 L/min) @ 80 psi
Connection Type: 1/2" IPS
Diverter Outlets: 2
Cartridge Type: Thermostatic

IAPMO, ASME A112.18.1/CSA B125.1, ASSE 1016 Type T, Massachusetts Accepted, LISTED ID: SH441081BN, SH441081CP, SH441081ORB



ADDITIONAL FEATURES

- Shower system includes wall mount rainfall shower head, wall-mount slide bar with hand shower, hand shower water connection and a thermostatic 2-way in-wall diverter.
- Thermostatic technology keeps shower temperature ± 1 degree Celsius.
- Hand shower water connection features a 1/2" IPS connection.
- 2-way diverter features 1/2" IPS inlets, and controls water flow between 2 shower outlets.
- Slide bar center-to-center measurement: 27-3/4".
- Slide bar overall height: 29-1/2".
- Slide bar base plate diameter: 1".
- Hand shower spray area: 3/8" W x 2-3/8" L.
- Diverter includes the valve and metal lever handles.
- The diverter allows operation of two spray functions at the same time.

REVISED 2/27/2025