



# DUNAWAY ADJUSTABLE SHOWER DRAIN

## BEFORE INSTALLING

Read the following installation instructions carefully. Observe all local plumbing and building codes.

## INSTRUCTIONS

For the following instructions it is assumed that the shower pan and drain flange coupling are already in place. Your application and conditions may call for variations to these procedures. Signature Hardware accepts no liability for any damage to floor, walls, plumbing, etc., or for personal injury during installation. We recommend consulting a professional if you are unfamiliar with installing bathroom fixtures and plumbing.

Unpack and inspect the drain and parts for damage. If damage is found, please call customer service at 1-866-855-2284. If you need assistance while installing your shower drain, contact customer service.

## TOOLS AND MATERIALS:



Silicone Sealant



Level



Thinset Mortar



Pea Gravel  
(32 ounces)

## INSTALLATION

1. Install the drain flange coupling to the underfloor plumbing.
2. Place pea gravel over the drain flange coupling weep holes and around the perimeter to prevent mortar from filling and blocking the holes.
3. Thread the adjustable drain barrel into the installed drain flange coupling. Apply a generous amount of 100% neutral cure silicone sealant to the underside of the lip of the drain barrel to ensure a watertight seal. Tighten firmly.
4. Attach the square drain trim piece to the installed drain barrel.
5. Insert the round drain trim piece into the square trim piece, and secure to the drain barrel using the provided brass screws.

