

D U C T M A T E

PRO seal[®]



& FIBER seal[®]



**UNION
MADE IN THE
USA**

Water Based High Velocity Duct Sealant

Low Brush Drag and Spreadability Reduces Labor Cost

- Indoor/outdoor grade
- For applications up to 15" W.G.
- Highly crack resistant
- Comes in fiber and non-fiber
- UL 181 B-M Listed
- UL 723 Classified
- LEED[®] Compliant
- Remains flexible

D **DUCTMATE**[®]
Industries, Inc.

GASKETS, SEALANTS, ADHESIVES

PROseal® & FIBERseal®

Premium Water Based High Velocity Duct Sealant

DESCRIPTION

PROseal and FIBERseal are premium water based high-velocity duct sealants.

BASIC USE

To seal metal joints against air leaks in low, medium, and high pressure duct systems

SPECIAL CHARACTERISTICS

- Indoor/outdoor grade
- For applications up to 15" w.g.
- Low brush drag and spreadability
- Permanently seals metal duct joints
- Highly crack resistant
- Remains flexible
- Excellent UV, water, and mold resistance
- Paintable with latex or epoxy based paint
- Will not drip or sag
- Mild odor
- UL 181B-M Listed
- UL 723 Classified
- LEED® Compliant
- Conforms to requirements of NFPA 90A and 90B
- Manufactured by S.M.W.I.A. Local 12
- Comes in fiber and non-fiber

DESCRIPTION

Surface Preparation: For good brushability, store at room temperature at least 24 hours before applying. Surfaces should be clean, dry and free of any dirt, oil, grease, water or foreign matter.

Application: (DO NOT THIN) Do not apply when rain or freezing temperatures will occur within 36 hours.

When Used In Conjunction With Sheet Metal: Apply by brush, hand, trowel or spray. PROseal and FIBERseal should be applied to duct connections according to all applicable SMACNA standards. Apply to the inside of female fittings and outside of male fittings. Assemble the joint.

Brush sealant over the assembled joint. Thoroughly cover joint and screws with a 2" to 3" wide band. Assembly should cure for 24-72 hours before pressure testing the system. Since field temperature/ humidity conditions may vary, longer set times may be required for specific installations. Apply at a rate of 50 sq. ft. per gallon (1/32" thick).

When Used In Conjunction With UL 181 Listed Flexible Air Ducts: Apply by brush a 1/16" (25 sq.ft. per gallon) coating and allow to dry a minimum of 24-72 hours. Since field temperature/humidity conditions may vary, longer set times may be required for specific installations. Use with mechanical fasteners per Air Duct installation instructions.

Clean Up: Use warm, soapy water to clean up sealant while it is still wet.

When Used In Conjunction With Duct Cover: Allow the sealant to cure fully before encapsulating duct ends with ProGuard, or any duct cover products. You may set the duct upright on a palate and encapsulate just the top, allowing air to flow through the bottom until the sealant has cured.



CAULKINGS AND SEALANTS SURFACE BURNING CHARACTERISTICS AS APPLIED TO INORGANIC REINFORCED CEMENT BOARD 51RF

	PROseal	FIBERseal
FLAME SPREAD:	0	5
SMOKE DEVELOPED:	0	5

Applied to Inorganic Reinforced Cement Board+
Tested as applied in two 2 in. wide strips 8 in. on center covering 16 percent of the test sample area at a coverage rate of 25 sq. ft. per gal.

TECHNICAL INFORMATION

BASE:	Synthetic latex emulsion (PROseal & FIBERseal) with fiber reinforcement (FIBERseal)
COLOR:	Gray
TYPE:	Water Base
WEIGHT:	11 ± .2 lbs per gallon
SOLID CONTENTS:	66% ± 2%
VISCOSITY:	350,000 c.p.s.
APPLICATION TEMPERATURE:	35°F to 110°F
SERVICE TEMPERATURE:	- 25°F to 200°F
STORAGE TEMPERATURE:	35°F to 110°F
DRY TO TOUCH:	1 hour (approximate)
CURE TIME:	24 to 72 hours + (depending on humidity, application, and temperature)
FLASH POINT:	No flash to boiling
WATER RESISTANCE:	Excellent
MILDEW RESISTANCE:	Excellent
FREEZE THAW STABILITY:	5 cycles
COVERAGE:	25 sq. ft./gal. at 1/16" 50 sq. ft./gal. at 1/32"
ODOR:	Mild (wet) None (dry)
SHELF LIFE:	1 year (unopened container)
CURED SEALANT:	Tough and permanently flexible
PACKAGING:	1/12 gallon tubes(25 tubes/case) 1 gallon pail (4 gal./case) 5 gallon pail 54 gallon drum

LIMITED PRODUCT WARRANTY

Ductmate warrants that PROseal® and FIBERseal®, when properly installed and maintained, will be free from defects in material and workmanship, and will comply with all written specifications made by Ductmate at the time of sale. Ductmate's warranty shall run for a period of one year from the date of manufacture.

Warranty Limitation:

The warranty stated above is in lieu of all other warranties, express or implied, including but not limited to the implied warranties of MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Although Ductmate may have suggested the product, or provided written or oral advice to the Purchaser, it is the Purchaser's responsibility to test and determine the suitability of PROseal® and FIBERseal®, for the intended use and purpose, and Purchaser and/or its customer assumes all risk and liability whatsoever regarding such suitability.

Limitation of Liability:

In the event of a breach of the above warranty, Ductmate's sole obligation, and Purchaser's sole and exclusive remedy, shall be, at Ductmate's option, repair or replacement of any defective products, or refund of an applicable portion of the purchase price. Ductmate shall have no liability for costs of removal or reinstallation of the product. The Purchaser agrees that no other remedy, including but not limited to loss of profits, loss sales, injury to person or property, or any other special, incidental or consequential damages, shall be available to the Purchaser for any claim arising out of this Agreement, regardless of whether such claim is made in contract or in tort, including strict liability in tort. In no event will Ductmate be obligated to pay damages to the Purchaser in any amount exceeding the purchase price that the Purchaser paid to Ductmate for the allegedly defective product.

KEEP OUT OF REACH OF CHILDREN. Consult MSDS (Material Safety Data Sheet) Before Using



Charleroi, PA

210 Fifth Street
Charleroi, PA 15022
800-245-3188
724-258-0500
FAX: 724-258-5494

Lodi, CA

810 S. Cluff Avenue
Lodi, CA 95240-9141
800-344-3270
209-333-4680
FAX: 209-333-4678

www.ductmate.com



This spec data is printed on paper that meets the Certified Fiber Sourcing requirements of the SFI program and contains 10% recycled content

Distributed By:

Ductmate is a proud member of the following organizations:



© Copyright Ductmate Industries, Inc. All rights reserved.

169-02/12