



TWIN CONTROL UTILITY SHOWER SET

INSTALLATION INSTRUCTIONS

Before installing, read entire Shower Set Installation Instructions. Observe all local building and safety codes.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1.866.855.2284. If you need assistance or have questions while installing your Shower Set, contact Customer Service.

Because wall construction and materials vary from home to home, Signature Hardware does not provide mounting hardware for all of our outdoor products. The appropriate mounting hardware can be purchased from your local hardware store.

We recommend consulting a professional if you are unfamiliar with installing outdoor and plumbing fixtures. Signature Hardware accepts no liability for any damage to the shower, installation surface, or for personal injury during installation.

TOOLS AND MATERIALS:

Adjustable Wrench

Pencil

Drill

Mounting Hardware

INSTALLATION

1. Slide the soap dish onto the riser pipe and hold in place.
2. Assemble the shower by attaching the riser to the hot and cold handle valve.
3. Thread the shower head onto the top of the riser. Make sure that the rubber washer is placed between the shower head and pipe to ensure a leak free connection.
4. Hold the shower in the desired mounting location. Mark the location of the mounting holes on the handle valve and soap dish.
5. Attach the shower to the mounting surface with the appropriate mounting hardware.
6. Connect the water supply to the outlets on the handle valve body.
7. Turn on the water supply to check for leaks. Let the water flow through the shower head for approximately 30 seconds to clear out debris and dirt. If leakage occurs, tighten connections with your adjustable wrench as necessary. If problems persist, contact Customer Service at 1-866-855-2284.