



Condenser Fan Motors - PSC

5 1/2 inch dia. MARS SERIES **098**



GE Commercial Motors

By Regal-Beloit



* Heat Shield



Vertical Outdoor Condenser Fan Motors Shaft-Up/Down


GE up/down outdoor condenser fan motors are designed for either vertical shaft-up or shaft-down applications. Shell and end shields are enclosed for weather protection. A weep hole is provided in each end shield to allow condensate to drain. A plastic plug is provided to seal the weep hole in the end shield exposed to the weather. All of these motors are suitable for air conditioning or heat pump applications. All feature reversible rotation, 208-230 volts, six inch shaft length and extended thru bolts extending from both ends.

Specifications:

- 60 Hertz
- Single phase
- Overload protected
- Fan duty, continuous, air over
- 26 inch leads
- Totally enclosed, non-ventilated
- Class B insulation

Features:

- Up/down design
- Thru bolt or band mounting
- All angle sleeve or ball bearings
- Water slinger on shaft
- Serrated end cap on shaft end only
- For air conditioning or heat pumps
- Full six inch shaft length with two full flats at 90°
- Reversible rotation
- For accessories, see pages M-73 to M-75



GE by RBC

Reversible Rotation

MARS NO.	GE NO.	HP	VOLTS	AMPS	RPM ⁽¹⁾	CAP REQ.	DIMENSIONS		
							A	B	C

825 RPM - Single Speed - Standard Efficiency - Ball Bearings - 8 Pole

03201	5KCP39EGL248S	1/10	208-230	0.80	825	5/370	6.0	4.30	1/2
03202*	5KCP39DFBA81S	1/8	208-230	1.10	825	5/370	6.0	4.30	1/2
03203*	5KCP39HFBA79S	1/6	208-230	1.00	825	5/370	6.0	4.30	1/2
03204*	5KCP39JFBA83	1/4	208-230	1.50	825	7.5/370	6.0	5.03	1/2
03205*	5KCP39NFBA82S	1/3	208-230	2.20	825	10/370	6.0	5.80	1/2
03747*	5KCP39TFBA84S	1/2	208-230	2.80	825	20/370	6.5	6.48	1/2

1075 RPM - Single Speed - Standard Efficiency - Ball Bearings - 6 Pole

03726*	5KCP39DGU716S	1/6	208-230	1.00	1075	5/370	6.5	3.98	1/2
03732 ⁽²⁾ *	5KCP39FGL114S	1/4	208-230	1.80	1075	5/370	6.0	4.23	1/2
03733 ⁽²⁾ *	5KCP39LGL786S	1/3	208-230	2.40	1075	7.5/370	6.0	4.48	1/2
03734 ⁽²⁾ *	5KCP39PGL787S	1/2	208-230	3.70	1075	10/370	6.0	5.23	1/2
03735 ⁽²⁾ *	5KCP39SGL788S	3/4	208-230	5.10	1075	10/370	6.0	5.98	1/2

(1) Low speed approximately 300 RPM less than high speed depending on fan load (2) Both end shields flat, no serrated end cap



The largest selection of motors, components and accessories for the HVAC/R Industry

M-41