

JONES STEPHENS' PLUMBITE® PUSH TO CONNECT SUPPLY STOPS

Product Description

A heat-free method of joining Copper, CPVC, PE-RT or PEX tubing, designed to save time on installation and to connect piping with relative ease and confidence. No soldering, glue, heat or external tools required to join the pipe. Just insert the pipe and the stainless steel gripper ring, bite down and hold the pipe tightly which the EPDM o-ring seals against leakage. Disassembly is just as fast using the optional disassembly tool so fittings can be easily removed and re-used.

Product Features

- Push to Connect Joining Technology (no Soldering, Glue, Heat or External Tools Required)
- Suitable for Copper, PEX, PE-RT or CPVC Piping systems
- Reduced installation time and cost
- Can be disassembled and re-used
- Secure Connections and Seal with Stainless Steel Gripper Ring and EPDM O-Ring
- Ideal for Piping Systems Service and Repair
- Full offering of 1/2" to 1" for most components
- Lead Free and Robust Brass Design, Certified for Potable Water Applications
- Individually packaged

Product Specifications

- NSF/ANSI 61 - Certification that this product does not leach harmful health contaminants into drinking water
- NSF/ANSI 372 - Certification to ensure the product lead content meets public safety standards
- UPC and cUPC - Meet Uniform Plumbing Code Requirements
- IAPMO Certified
- ASME A112.18.1/CSA B125.1

Performance Specifications

- Maximum Temperature - 180 degrees F
- Maximum Pressure - 200 PSI
- Service: Potable Water


Materials

- Body - DZR Brass
- O-Ring - EPDM, Peroxide Cured
- Gripper Ring - Stainless Steel
- Disassembly Tool (optional) - POM for sizes 1" and below, Stainless Steel for sizes 1-1/4" and higher




SUPPLY STOPS, STRAIGHT

Part Number Individually Packaged	Part Number Bulk Packaged	"A" Nominal (in.)	"B" Nominal (in.)	"C" (in.)	"C" Tolerance +/- (in.)
C77476LF	-	0.50	0.25 OD COMP	2.66	0.12
C77475LF	C76570LF	0.50	0.375 OD COMP	2.70	0.12



SUPPLY STOPS, ANGLE

Part Number Individually Packaged	Part Number Bulk Packaged	"A" Nominal (in.)	"B" Nominal (in.)	"C" (in.)	"C" Tolerance +/- (in.)
C77474LF	-	0.50	0.25 OD COMP	2.60	0.12
C77473LF	C76571LF	0.50	0.375 OD COMP	2.60	0.12



REDUCING TEE STOP

Part Number Individually Packaged	Part Number Bulk Packaged	"A" Nominal (in.)	"B" Nominal (in.)	"C" Nominal (in.)	"D" (in.)	"D" Tolerance +/- (in.)
C77445LF	-	0.75	0.75	0.25 OD COMP	3.04	0.12