

Use: For use in hot and cold domestic potable water systems.

Material Specifications

- · Made of ECO BRASS
- · Low-lead compliant
- · Made in USA

Operating Specifications

Temperature and Pressure: Tested to commercial hot water at 180°F and a pressure of 195 PSI



| SKU | Description | Length | Width | Height |
|-------------|-------------------------------------|--------|--------|--------|
| PFXPFDE9DD | LF 1/2 F1807 PEX X 1/2 FIP DE 90 EL | 2.105" | 1.450" | 1.250" |
| PFXPFDE9DF | LF 3/4 F1807 PEX X 3/4 FIP DE 90 EL | 2.468" | 2.103" | 1.925" |
| PFXPPFDE9DD | LF 1/2 F1960 PEX X 1/2 FIP DE 90 EL | 2.161" | 1.826" | 1.693" |
| PFXPPFDE9DF | LF 3/4 F1960 PEX X 3/4 FIP DE 90 EL | 2.780" | 2.103" | 1.925" |

Listings & Certifications

Low Lead Compliant and product CSA certified to NSF/ANSI 372 – Drinking water system components – Lead Content, and conforms to the requirements for "lead free" plumbing products as defined by California, Vermont, Maryland, and Louisiana state law and by Section 1417 of the US Safe Drinking Water Act.



