

DESCRIPTION

Floor-Mounted 1.28 gpf (4.8 Lpf) ADA 12" Rough-in Pressure-Assisted/Tank Toilet.

COMPONENTS

- Bowl: Code 2108029
- Tank: Code 2108110

DETAILS

- Flush Volume: 1.28 gpf (4.8 Lpf)

FEATURES

- White Vitreous China
- Elongated bowl
- Floor mounted, floor outlet
- 12" (305mm) rough-in
- Chrome metal flush handle
- Secure, anti-rocking 3-point tank mounting system
- Powered by Flushmate® brand pressure assisted flushing technology to achieve 1,000g MaP score
- Over 60 ft (18.3 m) drainline carry performance
- Water spot area: 11 ¼ x 9¾ (286 mm x 248 mm)
- Smooth, quiet cable activated flush handle - right hand
- Fully glazed trapway
- Closet bolts and caps included
- Toilet seat and wax ring not included

PLUMBING SYSTEM REQUIREMENTS

- Maximum Static Pressure: 80 PSI (552 kPa)
- Minimum Static Pressure: 20 PSI (138 kPa)

DOWNLOADS

- [Pressure-Assisted Installation Instructions](#)
- [Flushmate Owner's Manual](#)
- [Pressure-Assisted Repair and Maintenance Guide](#)
- [Additional Downloads](#)

**COMPLIANCES & CERTIFICATIONS**

CALGreen



(ADA Compliant, CalGreen Compliant, CEC Compliant, cUPC Green Certified, WaterSense Listed, NOM Certified)

NOTES

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

All information contained within this document subject to change without notice.

WARRANTY

[View Warranty Information](#)

Technical drawings of a toilet showing side, front, and top views with dimensions in inches and millimeters.

Side View Dimensions:

- Flush valve height: $\frac{3}{4}$ " (18)
- Seat height: $2\frac{3}{4}$ " (68)
- Water supply connection: 9" (229)
- Overall length: $30\frac{3}{8}$ " (771)
- Distance from wall to centerline: 19" (483)
- Distance from wall to front edge: 12" (305)
- Distance from wall to back edge: $17\frac{1}{8}$ " (434)
- Overall height: 17" (431)

Front View Dimensions:

- Top rim width: $18\frac{1}{4}$ " (462)
- Inner bowl width: $14\frac{3}{4}$ " (376)
- Distance from floor to bottom of bowl: 10" (254)
- Distance from floor to top of bowl: $29\frac{5}{8}$ " (754)
- Distance from wall to centerline: 6" (152)

Top View Dimensions:

- Distance between mounting holes: 6" (152)
- Overall width: 10" (254)
- Overall length: $22\frac{3}{8}$ " (568)

Page 2 of 2