CSB9120SJ

GE Café[™] Series 30" Single Wall Oven with Advantium[®] Technology

ADVANTIUM WALL OVEN/GE CAFÉ™ SERIES COOKING **TOWER DIMENSIONS AND CABINET INSTALLATION INFORMATION (IN INCHES)**

NOTE: Cabinets installed adjacent to wall ovens must have an adhesion spec of at least a 194°F temperature rating.

NOTE: 2" minimum between cutouts when installed above warming drawer or single wall oven.

INSTALLATION INFORMATION:

Before installing, consult installation instructions packed with product for current dimensional data.

spec of at least 194° F temperature rating 4-3/16" Cabinet width Junction box location 19-1/8" 21-1/2" To back 2-1/2" MIN between cutouts recommended-2" MIN required 29-3/4" Construct Solid Bottom Conduit MIN 3/8" Plywood Supported by 2 x 4 or 1 x 2 Runners, all Four Sides. (Must Support 150 lbs. for Advantium) (Must Support 200 lbs. for Wall Oven) 9-1/4" cutout height 28-1/2" cutout width 2" MIN between cutouts " Min. above toekick or adjust to oven installation height

3/8" Plywood Supported by 2 x 4 or 1 x 2 Runners, all Four Sides. 29-3/4" (Must Support 5" min.from 150 lbs.) floor 1" min. above toekick 30" A= Allow 1" overlap of oven over bottom edge of cutout, and allow

25-1/8"

Cutout width

Conduit

48-1/2

long)

23-1/2"

Cutout depth

17-1/2"

Cutout heigh

→ 4-3/16"

Junction

box location

Construct Solid

Bottom Min.

Note: Cabinets installed adjacent

to wall ovens must have an adhesion


1/8"

21-1/2" Back of Control

1-1/4" overlap at top edge of cutout. B= Allow 11/16"-3/4" for overlap of oven over side edges of cutout.

NOTE: Advantium wallovens can be installed below GE/GE Profile Series nondowndraft gas and electric cooktops. It CANNOT be installed below induction or Monogram (2GU3841385) gas cooktops.

NOTE: Advantium wall oven comes with two lower trim pieces. One is for use above 36-inch height installations and one is for use below 36-inch installations. Use of the accessory drawer will replace the bottom trim piece for applicable installations. Please see installation instructions for full details.





CSB9120SJ

GE Café[™] Series 30" Single Wall Oven with Advantium[®] Technology

PREPARATION WITH AN ACCESSORY DRAWER


PREPARE THE OPENING

The Advantium 120V can be installed in combination with other GE/Monogram appliances. Always follow each product's Installation Instructions to compete the installation.

SINGLE OVEN INSTALLATION:

Order a 30" wide single oven cabinet or cut the opening in a wall to the dimensions shown.

- * For existing cutouts, a maximum width of 28-1/2" is acceptable. If the opening is slightly wider, secure a furring strip on each side of the cutout for securing the oven.
- Allow 3/4" to 2-1/8" case trim overlap on the sides and 7/8" overlap on the bottom of the opening for all models. The amount of overlap on the sides depends on the actual cutout width. Allow 1-1/4" case trim



overlap on the top for models PSB9120 and for models ZSC1201 and ZSC1202.

• Oven overlaps will conceal cut edges on all sides of the opening.

NOTE: PSB9120 series Advantium can be installed below GE/GE Profile non-downdraft gas and electric cooktops. It CANNOT be installed below induction or Monogram (2GU3841385) gas cooktops.


NOTE: PSB9120 series Advantium oven comes with two lower trim pieces. One is for use above 36-inch height installations and one is for use below 36-inch installations. Use of the accessory drawer will replace the bottom trim piece for applicable installations. Please see installation instructions for full details.

PREPARE THE OPENING (CONT.)

When installed over a single oven or a warming drawer, allow at least 2" between the two openings. This separation will provide clearance for bottom overlap of the Advantium and the other appliance overlaps.


Construct a solid oven floor of 3/8" min. thick plywood supported by 2 x 4 or 2 x 2 runners on all sides.

• The support must be level and rigidly mounted, flush with the bottom edge of the cutout.



NOTE: Additional clearances between the cutouts may be required. Check to be sure the oven supports above the Warming Drawer location do not obstruct the required interior depth and height. See Warming Drawer installation instructions for details.

INSTALLATION OVER A GE/ MONOGRAM OVEN AND WARMING DRAWER:



NOTE: Additional clearances between the cutouts may be required. Check to be sure the oven supports above the Warming Drawer location do not obstruct the required interior depth and height. See Warming Drawer installation instructions for details.

CAUTION: For personal safety, the mounting surface must be capable of supporting the cabinet load, in addition to the added weight of this approximate 80-pound oven and 30-pound drawer, plus additional oven loads of up to 50 pounds or a total weight of 160 pounds.



CSB9120SJ

GE Café[™] Series 30" Single Wall Oven with Advantium[®] Technology

FEATURES AND BENEFITS

- Speedcook oven (120V) Enjoy oven-quality results two to four times faster than a conventional oven
- Multiple cooking functions Expand your cooking versatility with an all-in one oven
- Halogen heat Skip the preheating with nearly instantaneous halogen heat
- \bullet Over 175 preprogrammed menu selections Preprogrammed selections make meals easy
- \bullet Custom recipe saver Conveniently store cooking instructions for up to 30 different recipes
- Allows for use with JX2200/2201 storage drawer
- Under-the-counter installation flexibility
- Model CSB9120SJSS Stainless steel

