

Multi-Flo™ SYNTHETIC

Nominal Size W x H x D	Actual Size	NHM No Header Part #	FM Single Header Part #	Airflow Capacity (CFM)	Initial Resistance (inches w.g.)		NHM Media Area (sq. ft.)	SBM/FM Media Area (sq. ft.)
					NHM	FM		
MERV 15 (90-95%)								
24x24x12	23.38x23.38x11.50	112-650-001	112-660-001	2000	.58 .59	61	55	
12x24x12	11.38x23.38x11.50	112-650-002	112-660-002	1000	.58 .59	30	24	
24x24x6	23.38 x23.38x5.88	112-650-003	112-660-003	1000	.58 .59	33	29	
12x24x6	11.38x23.38x5.88	112-650-004	112-660-004	500	.58 .59	16	13	
20x20x12	19.38x19.38x11.50	112-650-005	112-660-005	1400	.58 .59	42	37	
20x24x12	19.38x23.38x11.50	112-650-006	112-660-006	1667	.58 .59	50	44	
20x24x6	19.38x23.38x5.88	112-650-007	112-660-007	834	.58 .59	27	24	
20x20x6	19.38x19.38x5.88	112-650-008	112-660-008	700	.58 .59	23	20	
MERV 14 (80-85%)								
24x24x12	23.38x23.38x11.50	112-651-001	112-661-001	2000	.45 .56	61	55	
12x24x12	11.38x23.38x11.50	112-651-002	112-661-002	1000	.45 .56	30	24	
24x24x6	23.38 x23.38x5.88	112-651-003	112-661-003	1000	.45 .56	33	29	
12x24x6	11.38x23.38x5.88	112-651-004	112-661-004	500	.45 .56	16	13	
20x20x12	19.38x19.38x11.50	112-651-005	112-661-005	1400	.45 .56	42	37	
20x24x12	19.38x23.38x11.50	112-651-006	112-661-006	1667	.45 .56	50	44	
20x24x6	19.38x23.38x5.88	112-651-007	112-661-007	834	.45 .56	27	24	
20x20x6	19.38x19.38x5.88	112-651-008	112-661-008	700	.45 .56	23	20	
Nominal Size W x H x D	Actual Size	NHM No Header Part #	FM Single Header Part #	Airflow Capacity (CFM)	Initial Resistance (inches w.g.)		NHM Media Area (sq. ft.)	SBM/FM Media Area (sq. ft.)
					NHM	FM		
MERV 11 (60-65%)								
24x24x12	23.38x23.38x11.50	112-652-001	112-662-001	2000	.33 .34	61	55	
12x24x12	11.38x23.38x11.50	112-652-002	112-662-002	1000	.33 .34	30	24	
24x24x6	23.38 x23.38x5.88	112-652-003	112-662-003	1000	.33 .34	33	29	
12x24x6	11.38x23.38x5.88	112-652-004	112-662-004	500	.33 .34	16	13	
20x20x12	19.38x19.38x11.50	112-652-005	112-662-005	1400	.33 .34	42	37	
20x24x12	19.38x23.38x11.50	112-652-006	112-662-006	1667	.33 .34	50	44	
20x24x6	19.38x23.38x5.88	112-652-007	112-662-007	834	.33 .34	27	24	
20x20x6	19.38x19.38x5.88	112-652-008	112-662-008	700	.33 .34	23	20	
MERV 10 (40-45%)								
24x24x12	23.38x23.38x5.88	112-653-001	112-663-001	2000	.32 .33	61	55	
12x24x12	11.38x23.38x5.88	112-653-002	112-663-002	1000	.32 .33	30	24	
24x24x6	23.38 x23.38x5.88	112-653-003	112-663-003	1000	.32 .33	33	29	
12x24x6	11.38x23.38x5.88	112-653-004	112-663-004	500	.32 .33	16	13	
20x20x12	19.38x19.38x11.50	112-653-005	112-663-005	1400	.32 .33	42	37	
20x24x12	19.38x23.38x11.50	112-653-006	112-663-006	1667	.32 .33	50	44	
20x24x6	19.38x23.38x5.88	112-653-007	112-663-007	834	.32 .33	27	24	
20x20x6	19.38x19.38x5.88	112-653-008	112-663-008	700	.32 .33	23	20	

- Average Efficiency: ASHRAE 52.1-1992 and 52.2-2007 test standard • Final Resistance: 1.5" W.G.
- Rated Velocity: 500 FPM - 12" Deep • Rated Velocity: 250 FPM - 6" Deep
- Maximum Operating Temperature: 180 degrees Fahrenheit and 82 degrees Celsius