


Submitted Model No.: _____ Specific Features:



▲ Designate Proper Finish Suffix



see what Delta can do

SLIDE BAR **HAND SHOWER**

■ Single Spray Setting

FEATURES:

- H₃Okinetic® Technology
- Lumicoat[™] Finish (-PR models only)
- Lumicoat[™] Finishes easily wipe clean without cleaners and chemicals on the products most commonly touched areas

- **STANDARD SPECIFICATIONS** Max flow rate 1.75 gpm @ 80 psi,6.6 L/min @ 550 kPa
- Certified dual check valves for backflow protection
- Hand held shower with single spray setting
- Spray face rotates 360 degrees
- 60" 82" (1524 mm 2083 mm) stretchable metal hose
- Wall bar bracket for hands-free showering
- Wall bar w/adjustable slide (allows for adjustable shower height). Not to be used as a grab bar.

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1 ◆
- ASME A112.18.3
- EPA WaterSense®
- Your Delta Faucet hand shower incorporates a beita Factet final shower interpolates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.