JONES STEPHENS

RUBBER PIPE INSULATION



Seamless Rubber Pipe Insulation

FM FM MADE IN THE

3/8" WA	LL THICKNE	SS CT	S APPROVED	Stronger Walder School Color	SA
PART NO.	Insulation Nominal ID	CTS (Nom. ID Plumbing)	CTS (OD HVAC/R)	IPS	FT/ BOX
160025	1/4"	1/8"	1/4"		630'
160038	3/8"	1/4"	3/8"	1/8"	612'
160050	1/2"	3/8"	1/2"	1/4"	432'
160058	5/8"	1/2"	5/8"	3/8"	378'
160075	3/4"	5/8"	3/4"		342'
160078	7/8"	3/4"	7/8"	1/2"	288'
160118	1-1/8"	1"	1-1/8"	3/4"	216'
160138	1-3/8"	1-1/4"	1-3/8"	1"	168'
160158	1-5/8"	1-1/2"	1-5/8"	1-1/4"	150'
160200	2"			1-1/2"	120'
160218	2-1/8"	2"	2-1/8"		96'
160250	2-3/8"			2"	84'
160258	2-5/8"	2-1/2"	2-5/8"		72'
160300	2-7/8"			2-1/2"	60'
160210	2 1 /0"	2"	2 1 /0"		CO!

1/2" WALL THICKNESS

PART NO.	Insulation Nominal ID	CTS (Nom. ID Plumbing)	CTS (OD HVAC/R)	IPS	FT/ BOX
I61025	1/4"	1/8"	1/4"		510'
I61038	3/8"	1/4"	3/8"	1/8"	456'
I61050	1/2"	3/8"	1/2"	1/4"	360'
I61058	5/8"	1/2"	5/8"	3/8"	324'
I61075	3/4"	5/8"	3/4"		270'
I61078	7/8"	3/4"	7/8"	1/2"	228'
I61118	1-1/8"	1"	1-1/8"	3/4"	156'
I61138	1-3/8"	1-1/4"	1-3/8"	1"	120'
I61158	1-5/8"	1-1/2"	1-5/8"	1-1/4"	114'
I61200	2"			1-1/2"	114'
I61218	2-1/8"	2"	2-1/8"		102'
I61250	2-3/8"			2"	66'
I61258	2-5/8"	2-1/2"	2-5/8"		60'
I61300	2-7/8"			2-1/2"	48'
I61318	3-1/8"	3"	3-1/8"		48'
I61350	3-1/2"			3"	36'
I61358	3-5/8"	3-1/2"	3-5/8"		36'
I61418	4-1/8"	4"	4-1/8"	3-1/2"	24'
I61450	4-1/2"			4"	24'

3/4" WALL THICKNESS

PART NO.	Insulation Nominal ID	CTS (Nom. ID Plumbing)	CTS (OD HVAC/R)	IPS	FT/ BOX
162025	1/4"	1/8"	1/4"		240'
162038	3/8"	1/4"	3/8"	1/8"	228'
162050	1/2"	3/8"	1/2"	1/4"	228'
162058	5/8"	1/2"	5/8"	3/8"	180'
162075	3/4"	5/8"	3/4"		144'
162078	7/8"	3/4"	7/8"	1/2"	126'
I62118	1-1/8"	1"	1-1/8"	3/4"	90'
I62138	1-3/8"	1-1/4"	1-3/8"	1"	78'
I62158	1-5/8"	1-1/2"	1-5/8"	1-1/4"	72'
162200	2"			1-1/2"	66'
I62218	2-1/8"	2"	2-1/8"		60'
162250	2-3/8"			2"	48'
162258	2-5/8"	2-1/2"	2-5/8"		42'
162300	2-7/8"			2-1/2"	36'
I62318	3-1/8"	3"	3-1/8"		36'
162350	3-1/2"			3"	30'
162358	3-5/8"	3-1/2"	3-5/8"		30'
162418	4-1/8"	4"	4-1/8"	3-1/2"	24'
162450	4-1/2"			4"	24'

- Closed cell flexible elastomeric foam insulation tubes
- Seamless Non-slit for slide-on applications
- Self-Sealing (Pre-Slit / Pre-Glued / DoubleSeal closure system) for retrofit applications
- For use on HVAC/R, commercial, and industrial process piping and equipment
- For most indoor applications, no additional jacketing is required
- High resistance to moisture vapor intrusion; low thermal conductivity
- CARTON OUANTITIES ONLY

SPECIFICATIONS:

Temp Range: -297°F (-183°C) to +220°F (+104°C) Flame/Smoke: ASTM E84 25/50-rated (to 2") Water Vapor Permeability: <0.01 perm-in

Density: 3-6 lb/cubic ft Mold growth: None Ozone Resistance: Good

1"WALL THICKNESS

PART NO.		CTS (Nom. ID	CTS (OD	IPS	FT/
	Nominal ID	Plumbing)	HVAC/R)		BOX
163025	1/4"	1/8"	1/4"		120'
163038	3/8"	1/4"	3/8"	1/8"	120'
163050	1/2"	3/8"	1/2"	1/4"	114'
163058	5/8"	1/2"	5/8"	3/8"	108'
163075	3/4"	5/8"	3/4"		108'
163078	7/8"	3/4"	7/8"	1/2"	90'
I63118	1-1/8"	1"	1-1/8"	3/4"	66'
163138	1-3/8"	1-1/4"	1-3/8"	1"	60'
163158	1-5/8"	1-1/2"	1-5/8"	1-1/4"	54'
163200	2"			1-1/2"	42'
163218	2-1/8"	2"	2-1/8"		42'
163250	2-3/8"			2"	36'
163258	2-5/8"	2-1/2"	2-5/8"		36'
163300	2-7/8"			2-1/2"	36'
163318	3-1/8"	3"	3-1/8"		30'
163350	3-1/2"			3"	30'
163358	3-5/8"	3-1/2"	3-5/8"		30'
163418	4-1/8"	4"	4-1/8"	3-1/2"	18'

1-1/2" WALL THICKNESS

PART NO.	Insulation Nominal ID	CTS (Nom. ID Plumbing)	CTS (OD HVAC/R)	IPS	FT/ BOX
164050	1/2"	3/8"	1/2"	1/4"	48'
164058	5/8"	1/2"	5/8"	3/8"	48'
164075	3/4"	5/8"	3/4"		48'
164078	7/8"	3/4"	7/8"	1/2"	48'
164118	1-1/8"	1"	1-1/8"	3/4"	36'
164138	1-3/8"	1-1/4"	1-3/8"	1"	36'
164158	1_5/8"	1_1/2"	1_5/8"	1_1 ///"	36'

See reverse side for additional product listing!



RUBBER PIPE INSULATION

MADE IN THE

Double Stick Rubber Pipe Insulation



3/8" WA	LL THICKNI	ss (US	APPROVED	USA
PART NO.	Insulation Nominal ID	CTS (Nom. ID Plumbing)	CTS (OD HVAC/R)	IPS	FT/ BOX
180038	3/8"	1/4"	3/8"	1/8"	570'
180058	5/8"	1/2"	5/8"	3/8"	348'
180034	3/4"	5/8"	3/4"		318'
180078	7/8"	3/4"	7/8"	1/2"	288'
180118	1-1/8"	1"	1-1/8"	3/4"	216'
180138	1-3/8"	1-1/4"	1-3/8"	1"	150'
180150	2"			1-1/2"	120'
180158	1-5/8"	1-1/2"	1-5/8"	1-1/4"	132'
180218	2-1/8"	2"	2-1/8"		78'
180200	2-3/8"			2"	78'

1/2" WALL THICKNESS

PART NO.	Insulation	CTS (Nom. ID	CTS (OD	IPS	FT/
	Nominal ID	Plumbing)	HVAC/R)		BOX
181038	3/8"	1/4"	3/8"	1/8"	420'
I81050	1/2"	3/8"	1/2"	1/4"	312'
181058	5/8"	1/2"	5/8"	3/8"	312'
I81034	3/4"	5/8"	3/4"		270'
I81078	7/8"	3/4"	7/8"	1/2"	216'
181118	1-1/8"	1"	1-1/8"	3/4"	150'
I81138	1-3/8"	1-1/4"	1-3/8"	1"	120'
I81150	2"			1-1/2"	108'
I81158	1-5/8"	1-1/2"	1-5/8"	1-1/4"	108'
I81218	2-1/8"	2"	2-1/8"		102'
181200	2-3/8"			2"	60'
181258	2-5/8"	2-1/2"	2-5/8"		60'
I81250	2-7/8"			2-1/2"	48'
181318	3-1/8"	3"	3-1/8"		48'
I81300	3-1/2"			3"	36'
I81358	3-5/8"	3-1/2"	3-5/8"		36'
I81418	4-1/8"	4"	4-1/8"	3-1/2"	24'
181400	4-1/2"			4"	24'

3/4" WALL THICKNESS

PART NO.	Insulation	CTS (Nom. ID	CTS (OD	IPS	FT/
	Nominal ID	Plumbing)	HVAC/R)		BOX
182038	3/8"	1/4"	3/8"	1/8"	228'
182050	1/2"	3/8"	1/2"	1/4"	192'
182058	5/8"	1/2"	5/8"	3/8"	180'
182034	3/4"	5/8"	3/4"		120'
182078	7/8"	3/4"	7/8"	1/2"	126'
182118	1-1/8"	1"	1-1/8"	3/4"	90'
182100	1-3/8"	1-1/4"	1-3/8"	1"	78'
182158	1-5/8"	1-1/2"	1-5/8"	1-1/4"	72'
182150	2"			1-1/2"	66'
182218	2-1/8"	2"	2-1/8"		60'
182200	2-3/8"			2"	48'
182258	2-5/8"	2-1/2"	2-5/8"		42'
182250	2-7/8"			2-1/2"	36'
182318	3-1/8"	3"	3-1/8"		36'
182358	3-5/8"	3-1/2"	3-5/8"		30'
182418	4-1/8"	4"	4-1/8"	3-1/2"	24'
182400	4-1/2"			4"	24'

1"WALL THICKNESS

PART NO.	Insulation Nominal ID	CTS (Nom. ID Plumbing)	CTS (OD HVAC/R)	IPS	FT/ BOX
183058	5/8"	1/2"	5/8"	3/8"	108'
183034	3/4"	5/8"	3/4"		78'
183078	7/8"	3/4"	7/8"	1/2"	78'
I83118	1-1/8"	1"	1-1/8"	3/4"	66'
I83138	1-3/8"	1-1/4"	1-3/8"	1"	60'
183158	1-5/8"	1-1/2"	1-5/8"	1-1/4"	42'
183150	2"			1-1/2"	42'
183218	2-1/8"	2"	2-1/8"		42'
183200	2-3/8"			2"	36'
183250	2-7/8"			2-1/2"	36'
183358	3-5/8"	3-1/2"	3-5/8"		30'
I83418	4-1/8"	4"	4-1/8"	3-1/2"	18'

Rubber Insulation Roll

- Closed cell flexible elastomeric foam insulation rolls
- For use on HVAC/R and industrial process ductwork, vessels, equipment and large ID piping (>8" IPS)
- · High resistance to moisture vapor intrusion; low thermal conductivity
- For most indoor applications, no additional jacketing is required
- Available as S2S (skin-two-side)
- CARTON QUANTITIES ONLY



c FU °us	GRIENGLIMED INC. INC. INC. INC. INC. INC. INC. INC.	WADE IN THE
-----------------	--	-------------

PART NO.	DESCRIPTION	CTS (OD HVAC/R)	SQ FT/BOX
IR1470	1/2" thick x 4' x 70' roll	5/8"	280'
IR5415	2" thick x 4' x 15' roll	3/4"	60'

Titan™ Seamless UV Resistant Rubber Pipe Insulation



- Ideal for outdoor applications: UV resistant, tear resistant, weather resistant
- 1-Step Install: No field applied protective coating or additional jacketing required
- · CARTON QUANTITIES ONLY

1/2" WALL THICKNESS

PART NO.	Insulation	CTS (Nom. ID	CTS (OD	IPS	FT/
	Nominal ID	Plumbing)	HVAC/R)		BOX
191025	1/4"		1/4"		510'
191038	3/8"	1/4"	3/8"	1/8"	456'
191050	1/2"	3/8"	1/2"	1/4"	360'
191058	5/8"	1/2"	5/8"	3/8"	324'
I91075	3/4"	5/8"	3/4"		270'
191078	7/8"	3/4"	7/8"	1/2"	228'
I91118	1-1/8"	1"	1-1/8"	3/4"	156'
I91138	1-3/8"	1-1/4"	1-3/8"	1"	120'

3/4" WALL THICKNESS

PART NO.	Insulation Nominal ID	CTS (Nom. ID Plumbing)	CTS (OD HVAC/R)	IPS	FT/ BOX
192050	1/2"	3/8"	1/2"	1/4"	228'
192058	5/8"	1/2"	5/8"	3/8"	180'
192075	3/4"	5/8"	3/4"		144'
192078	7/8"	3/4"	7/8"	1/2"	126'
I92118	1-1/8"	1"	1-1/8"	3/4"	90'
I92138	1-3/8"	1-1/4"	1-3/8"	1"	78'
192158	1-5/8"	1-1/2"	1-5/8"	1-1/4"	72'

Visit www.jonesstephens.com for product specification sheets.

Contact your local Jones Stephens sales representative to order today!

