

PlumBite® Push On Tee

Job Name	_____
Location	_____
Engineer	_____
Contractor	_____
Tag	_____ PO# _____

Specifications

- A heat-free method of joining Copper, CPVC, PE-RT or PEX tubing. Fittings can be removed and re-used, using the disassembly tool (sold separately).

Applications

- Commercial and residential potable and non-potable water applications

Materials

- Body-DZR Brass
- O-Ring- EPDM, Peroxide Cured
- Gripper Ring- Stainless Steel



Dimensions and Product Offering

Part Code	Part Code Bulk	A -Nominal (in.)	B -Nominal (in.)	C -Nominal (in.)	D (in.)	D -Tolerance +/- (in.)
C77440LF	C76510LF	1/2	1/2	1/2	2.68	-
C77441LF	C76511LF	3/4	3/4	3/4	3.14	0.06
C77442LF	-	1	1	1	3.69	0.02

Performance Specifications

- Maximum Temperature: 180°F
- Maximum Pressure: 200 PSI
- Service: Potable Water
- Exposure to water with elevated levels of inorganic materials (including but not limited to: Cl, Na, Mg, Ca, K), especially in high temperatures and high water velocity areas, could quicken the corrosion process.

Certifications/Listings/Approvals

- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372
- NSF/ANSI 14
- IAPMO listed
- IAPMO certified for use in manufactured joints without access panels
- ASSE 1061

