

PlumBite® Push On Supply Stop, Straight

Job Name	_____
Location	_____
Engineer	_____
Contractor	_____
Tag	_____ PO# _____

Specifications

- A heat-free method of joining Copper, CPVC, PE-RT or PEX tubing. Fittings can be removed and re-used, using the disassembly tool (sold separately).

Applications

- Commercial and residential potable and non-potable water applications

Materials

- Gasket- EPDM, Peroxide Cured
- Valve Body- Brass

Dimensions and Product Offering

Part Code	Part Code Bulk	A -Nominal (in.)	B -Nominal (in.)	C -(in.)	C -Tolerance +/- (in.)
C77476LF	-	1/2	1/4 OD COMP	2.56	0.02
C77475LF	C76570LF	1/2	3/8 OD COMP	2.53	0.05

Performance Specifications

- Maximum Temperature: 180°F
- Maximum Pressure: 200 PSI
- Service: Potable Water
- Exposure to water with elevated levels of inorganic materials (including but not limited to: Cl, Na, Mg, Ca, K), especially in high temperatures and high water velocity areas, could quicken the corrosion process.

Certifications/Listings/Approvals

- NSF/ANSI/CAN 61: Q
- NSF/ANSI/CAN 372
- NSF/ANSI 14
- ASME A112.18.1/CSA B125.1
- SDWA Compliant
- Lead Law Compliant
- MASS Approved
- Vermont Act 193 Compliant

