

PlumBite® Push On Stop Tee

Specifications

- A heat-free method of joining Copper, CPVC, PE-RT or PEX tubing. Fittings can be removed and re-used, using the disassembly tool (sold separately).

Applications

- Commercial and residential potable and non-potable water applications

Materials

- Gasket- EPDM, Peroxide Cured
- Valve Body- Brass
- Gripper Ring- Stainless Steel

Dimensions and Product Offering


Part Code	A -Nominal (in.)	B -Nominal (in.)	C -Nominal (in.)	D -Nominal (in.)	D -Tolerance +/- (in.)
C77445LF	3/4	3/4	1/4 OD COMP	3.00	.04

Performance Specifications

- Maximum Temperature: 180°F
- Maximum Pressure: 200 PSI
- Service: Potable Water
- Exposure to water with elevated levels of inorganic materials (including but not limited to: Cl, Na, Mg, Ca, K), especially in high temperatures and high water velocity areas, could quicken the corrosion process.

Certifications/Listings/Approvals

- NSF/ANSI/CAN 61: Q
- NSF/ANSI/CAN 372
- NSF/ANSI 14
- ASME A112.18.1/CSA B125.1
- SDWA Compliant
- Lead Law Compliant
- MASS Approved
- Vermont Act 193 Compliant



Job Name _____
Location _____
Engineer _____
Contractor _____
Tag _____ PO# _____

