

# PlumBite® Push On Reducing Adapter

## Specifications

- A heat-free method of joining Copper, CPVC, PE-RT or PEX tubing. Fittings can be removed and re-used, using the disassembly tool (sold separately).

## Applications

- Commercial and residential potable and non-potable water applications

## Materials

- Body-DZR Brass
- O-Ring- EPDM, Peroxide Cured
- Gripper Ring- Stainless Steel

## Dimensions and Product Offering


Part Code	Part Code Bulk	A -Nominal (in.)	B -Nominal (in.)	C -(in.)	C -Tolerance +/- (in.)
<b>C77420LF</b>	-	1/2	3/4 MPT	1.73	0.01
<b>C77421LF</b>	-	3/8	1/2 MPT	1.73	0.08
<b>C77422LF</b>	-	1/2	3/4 FPT	1.63	0.01
<b>C77423LF</b>	-	3/8	1/2 FPT	1.58	0.08

## Performance Specifications

- Maximum Temperature: 180°F
- Maximum Pressure: 200 PSI
- Service: Potable Water
- Exposure to water with elevated levels of inorganic materials (including but not limited to: Cl, Na, Mg, Ca, K), especially in high temperatures and high water velocity areas, could quicken the corrosion process.

## Certifications/Listings/Approvals

- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372
- NSF/ANSI 14
- IAPMO listed
- IAPMO certified for use in manufactured joints without access panels
- ASSE 1061



<b>Job Name</b> _____
<b>Location</b> _____
<b>Engineer</b> _____
<b>Contractor</b> _____
<b>Tag</b> _____ <b>PO#</b> _____

