

PlumBite® Push On Water Heater Connector

Specifications

- A heat-free method of joining Copper, CPVC, PE-RT or PEX tubing. Fittings can be removed and re-used, using the disassembly tool (sold separately).

Applications

- Commercial and residential potable and non-potable water applications

Materials

- Body-DZR Brass
- O-Ring- EPDM, Peroxide Cured
- Gripper Ring- Stainless Steel

Dimensions and Product Offering

Part Code	A -Nominal (in.)	B -Nominal (in.)	C -(in.)	C -Tolerance +/- (in.)
C76605LF	3/4 FIP	1/2	12.52	0.39
C76607LF	3/4 FIP	1/2	18.55	0.40
C76608LF	3/4 FIP	1/2	24.53	0.40
C76612LF	3/4 FIP	3/4	12.52	0.39
C76613LF	3/4 FIP	3/4	15.52	0.40
C76614LF	3/4 FIP	3/4	18.55	0.40
C76615LF	3/4 FIP	3/4	24.53	0.40
C77478LF	3/4 FIP	3/4	18.21	0.01
C77479LF	3/4 FIP	3/4	24.32	0.13

Performance Specifications

- Maximum Temperature: 180°F
- Maximum Pressure: 200 PSI
- Service: Potable Water
- Exposure to water with elevated levels of inorganic materials (including but not limited to: Cl, Na, Mg, Ca, K), especially in high temperatures and high water velocity areas, could quicken the corrosion process.

Certifications/Listings/Approvals

- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372
- ASME A112.18.6/CSA B125.6
- Vermony Act Compliant
- SDWA Compliant
- Lead Law Compliant
- MASS Approved



Job Name _____
Location _____
Engineer _____
Contractor _____
Tag _____ PO# _____

