Spyn LED 52" Fan Anvil Iron

© 2021 Kichler Lighting LLC. All Rights Reserved.

300275AVI

MOTOR FINISH



BLADE FINISHES





AIR PERFORMANCE

	RPM Revolutions Per Minute on High 162	POWER USAGE Watts on High (Excludes Lights) 63	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt 80	CFM (Low) RPM (Low) Watts (Low)	2026 63 11
--	---	--	---	---------------------------------------	------------------

SPECIFICATIONS

Light Source			
Downward-facing Bulbs Downlight Included Watts (High)	1 X 17W Yes 63	Dimmable Downlight Option Watts (Low)	Yes Integrated 11
Photometrics			
Color Rendering Index	80	Kelvin Temperature	3000K
Electrical			
Amps (High) Motor Size	0.53 153MM X 17MM	Amps (Low) Motor Type	0.21 AC
Dimensions			
Base Backplate Weight Width	6.00 DIA 13.54 LBS 52.00"	Downrod 1 Height	1.00 OD X 6.00" 14.50"
Mounting/Installation			
Minimum Distance from Fan to Floor Lead Wire Length	7 feet 78"	Interior/Exterior Location Rating	Interior Dry
FIXTURE ATTRIBUTES			
Product/Ordering Information			
SKU Style	300275AVI Transitional	Finish UPC	Anvil Iron 783927559911
Housing			
Diffuser Description Max Stem Tilt	Etched Cased Opal 22 Degrees	Primary Material Wall Control Included	STEEL Yes



Blade Finish & Specs	cs
----------------------	----

Blade Finish 1 Blade Pitch Blade Sweep DSTRD ANTQ GRY 13 52 ABS Yes 3

Warranty www.kichler.com/warranty

ALSO IN THIS FAMILY





300275NI



300275WH

You can see all products in this family by searching Kichler.com

KICHLER