



MODA™ FIRE-RATED ICE MAKER SUPPLY BOX TECHNICAL SPECIFICATION


Job Name _____	Item # _____
Location _____	
Engineer _____	Contractor _____
PO # _____	Tag _____
Representative _____	

SPECIFICATIONS

Oatey MODA™ fire-rated ice maker supply boxes shall be used in residential or commercial applications requiring a supply valve recessed in the wall. The MODA™ fire-rated ice maker box assembly contains a 1/4" OD compression valve pre-installed in a PVC box, with inter-locking wing flanges on each side. The wing flanges in conjunction with the metal bracket allow for direct to stud installation. L-shape brackets are included for support based on wall rating (see instruction sheet). Valves shall be a two-piece design, permitting field replacement, and shall be secured with a stainless steel retention clip. Valves are available with or without water hammer arrestors and shall be installed upright. The assembly shall include an emergency drain port for protection from tubing leaks.

APPROVALS & LISTINGS

Valves	ASME A112.18.1 / CSA B125.1 NSF / ANSI 61 & 372
Water Hammer Arrestors	ASSE 1010, PDI WH 201
Boxes	IAPMO-Listed, PS-54
Listed with Massachusetts Board of Plumbing Listed by Warnock Hersey to meet: ASTM E814	
2-Hour Design	F-Rating: 2 Hour, T-Rating: 1-1/4 Hour
1-Hour Design	F-Rating: 1 Hour , T-Rating: 3/4 Hour
CAN/ULC S115	
2-Hour Design	FH Rating: 2 Hour, FTH Rating: 1-1/4 Hour
1-Hour Design	FH Rating: 1 Hour, FTH Rating: 3/4 Hour



Accessory Components Included:



Faceplate



Intumescent Pad
(Pre-installed)



Sticker Cover
(For Debris Protection)

FEATURES & MATERIALS

Outlet Box & Brackets	PVC
Valve Body	Forged Brass C46500 No Lead
Valve Retention Clip	Stainless Steel
Valve O-Rings	NSF Approved EPDM (2)
Metal Bracket and L-shape Brackets	16 Gauge Galvanized Steel
Arrestor Body	Copper (Type L)
Piston	Polypropylene with two NBR O-rings
Piston Lubrication	Dow Coming Molykote 111

PERFORMANCE SPECIFICATIONS

Temperature Rating (Valve)	250° F/121° C
Max Testing Pressure (Valve)	100 psi (Air)/250 psi (Water)

DIMENSIONS




[A]:	Box Width	7.98"	[E]:	Faceplate Depth	1.25"
[B]:	Box Height	8.46"	[F]:	Faceplate Width	6.00"
[C]:	Box Depth	3.63"	[G]:	Faceplate Height	6.45"
[D]:	Metal Bracket Height	8.87"			



Metal Bracket (1)



L-shape
Brackets (2)



Access BIM/Revit content through www.oatey.com



MODA™ FIRE-RATED ICE MAKER SUPPLY BOX TECHNICAL SPECIFICATION

PRODUCT SELECTOR

NO HAMMER ARRESTORS			HAMMER ARRESTORS		
✓	Product Number	Description	✓	Product Number	Description
	37378	IMOB, Copper, NoHam, Single Pack		37385	IMOB, Copper, Ham, Single Pack
	37379	IMOB, F1807-Brass, NoHam, Single Pack		37386	IMOB, F1807-Brass, Ham, Single Pack
	37380	IMOB, F2159-PPSU, NoHam, Single Pack		37387	IMOB, F2159-PPSU, Ham, Single Pack
	37381	IMOB, F1960-Brass, NoHam, Single Pack		37388	IMOB, F1960-Brass, Ham, Single Pack
	37382	IMOB, F1960-PPSU, NoHam, Single Pack		37389	IMOB, F1960-PPSU, Ham, Single Pack
	37383	IMOB, CPVC, NoHam, Single Pack		37390	IMOB, CPVC, Ham, Single Pack
	37384	IMOB, Push Cnc, NoHam, Single Pack		37391	IMOB, Push Cnc, Ham, Single Pack

All products sold in single case packs

Access BIM/Revit content through www.oatey.com