

Betello® Comfort Height®

Elongated chair height toilet bowl K-20148

Features

- Elongated bowl offers added room and comfort.
- Skirted trapway simplifies cleaning.
- Revolution 360[®] flushing technology generates a forceful swirling motion to keep the bowl clean longer.
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults.
- 2-1/8" (54 mm) glazed trapway.
- CleanCoat™ surface treatment inhibits the growth of water scale and mineral stains for improved ease of cleaning.
- Combines with the K-20203/-RA or K-20204 tank to create a complete K-20197/-RA Betello™ or K-20198 Betello™ ContinuousClean toilet.
- Patented ReadyLock® installation system, a simple solution for skirted toilets, saves time, hassle, and eliminates the need to drill into the floor for standard 12" (305 mm) rough-in.

Installation

- Standard 12" (305 mm) rough-in.
- 10" and 14" (254 mm and 356 mm) rough-in kits also available.
- Seat sold separately.

Recommended Products/Accessories

K-20203 Toilet tank, 1.28 gpf K-20203-RA Toilet tank, 1.28 gpf K-20204 1.28 gpf toilet tank with ContinuousClean XT technology K-23726 Drain treatment

Included Components

Additional Components: ReadyLock™ installation system





Codes/Standards

ASME A112.19.2/CSA B45.1 EPA WaterSense®

KOHLER® Toilets and Seats Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

| Color | Code | Description |
|-------|------|--------------|
| | 0 | White |
| | 96 | Biscuit |
| 3.3 | NY | Dune |
| | 95 | Ice™ Grey |
| | G9 | Sandbar |
| | 7 | Black Black™ |





Betello® Comfort Height®

Elongated chair height toilet bowl K-20148

No image available.

This product is a component and not intended to be a standalone installation.

Technical Information

All product dimensions are nominal. Toilet type: Floor-mount

Waste Outlet: Floor Bowl shape: Elongated Flush type: Revolution 360®

Water Consumption

Full: 1.28 gpf (4.8 lpf)

9-3/8" x 7-3/16" (238 mm x 183 mm) Water surface size:

Rough-in: 12" (305 mm)

Fixture Supply Requirements Min static pressure: 15 psi (103.4 kPa) Max static pressure: 80 psi (551.6 kPa)

Notes

Install this product according to the installation instructions.

