

FLEX YOUR COVERAGE.

FIND THE CORRECT CHAIN KNOCKER FOR THE JOB
TO GET WALL-TO-WALL CLEAN



FlexShaft is the new tool in the RIDGID Drain Cleaning Range and can help you solve a wide array of Drain issues of your customers. **Selecting the correct tool for FlexShaft is a crucial part of a clean drain solution.**

WHAT IS THE BLOCKAGE TO CLEAN?



SOFT BLOCKAGES
grease, soap, hair,



SEMI-HARD BLOCKAGES
Light Tree Roots, Plant Roots



HARD BLOCKAGES
Scale, Uric Scale, Limestone

SMOOTH CHAIN



Can be used in all types of Pipe such as
PVC, ABS, Copper, Cast...

K9-102:
1 Chain for 32-40 mm
2 Chains for 40-50 mm

CARBIDE TIPPED CHAIN



Can be used in Hard-Walled Pipe such as
Cast Iron, Copper, Galvanized
use with care in Soft-Walled pipe (e.g. PVC)

K9-204:
2 Chains for 50 mm
3 Chains for 75 mm
3 Chains for 100 mm

If the tools keep blocking into the blockage, consider use of another RIDGID Drain Cleaner



FLEX YOUR COVERAGE.

FIND THE RIGHT CHAIN KNOCKER FOR THE JOB TO GET WALL-TO-WALL CLEAN



K9-204 MACHINE

K9-102 MACHINE

Use below table for recommended options based on blockage, pipe size and pipe type.

		K9-102 MACHINE				K9-204 MACHINE					
		Chain Knockers		Carbide Tipped Chain Knockers		Chain Knockers			Carbide Tipped Chain Knockers		
		64293	64298	64283	64288	64323	64328	64333	64308	64313	64318
		K9-102 1.5"	K9-102 2"	K9-102 1.5" CARBIDE	K9-102 2" CARBIDE	K9-204 2"	K9-204 3"	K9-204 4"	K9-204 2" CARBIDE	K9-204 3" CARBIDE	K9-204 4" CARBIDE
		1.25"-1.5" (32-40 mm)	1.5"-2" (40-50 mm)	1.25"-1.5" (32-40 mm)	1.5"-2" (40-50 mm)	2" (50 mm)	3" (75 mm)	4" (100 mm)	2" (50 mm)	3" (75 mm)	4" (100 mm)
PIPE TYPE	COPPER	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	GALVANIZED	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	CAST IRON	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	PVC	✓	✓			✓	✓	✓			
	ABS	✓	✓			✓	✓	✓			
	ORANGEBURG	✓	✓			✓	✓	✓			
	CORRUGATED	✓	✓			✓	✓	✓			
	CLAY	✓	✓			✓	✓	✓			
BLOCKAGE	GREASE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	SOFT BLOCKAGE	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	SCALING			✓	✓				✓	✓	✓
	LIGHT ROOTS			✓	✓				✓	✓	✓
	INCLUDED WITH KIT	✓	✓			✓		✓			

Any chain knocker can be purchased separately.



Read manual for setup.

