

## BS50-4 BS60-4 BS70-4 Technical specifications

	BS50-4As	BS60-4As	BS70-4As
<b>Operating data</b>			
Operating weight lb	143	159	176.4
Ramming shoe size (WxL) in	11 x 13.4	11 x 13.4	11 x 13.4
L x W x H in	26.5 x 13.5 x 37	26.5 x 13.5 x 38	26.5 x 13.5 x 38
Percussion rate max. blows/min	680	690	678
Stroke at the ramming shoe in	2.2	3.1	2.9
Impact force lbf	3,597	4,047	4,496
Operating speed ft/min	23.3	28.9	23
Surface capacity - Compaction ft <sup>2</sup> /h	1,281	1,604	1,270
<b>Engine / Motor</b>			
Engine / Motor type	GXR 120	GXR 120	GXR 120
Engine / Motor manufacturer	Honda	Honda	Honda
Engine / Motor	Air-cooled single-cylinder four-cycle gasoline engine	Air-cooled single-cylinder four-cycle gasoline engine	Air-cooled single-cylinder four-cycle gasoline engine
Displacement in <sup>3</sup>	7.38	7.38	7.38
Operating performance (DIN ISO 3046-1) hp at rpm rpm	3.6 4,200	3.6 4,200	3.6 3,600
Fuel consumption US gal/h	0.26	0.26	0.26
Fuel tank capacity US gal	0.77	0.77	0.77
CO <sub>2</sub> (NRSC) * g/kW-hr	674	674	674

\*Determined value of the CO<sub>2</sub> emission during engine certification without consideration of the application on the machine.

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.  
Copyright © 2020 Wacker Neuson SE.