


120T Series Installation Checklist and Venting Table

Important - Read the installation and operation manual before installing and operating this water heater.

- ❑ **Product Handling** - Carefully uncrate the heater. Move in place with a pallet jack (don't use the venting pipes for handles). A 2 inch (5 cm) high installation pad is recommended.
- ❑ **Electrical Requirements** - Make sure there is a dedicated 120 volts line voltage and line power is properly polarized. Proper ground is required to this water heater.
- ❑ **Venting Requirements** - All venting must stay within the required lengths and diameters (see chart below). Proper support of the venting pipe is a **MUST** (every 5 feet (1.5 m) vertical and 3 feet (.9 m) horizontal). Terminations must be located to prevent re-circulation. Medium to long sweep 90° elbows are recommended.
- ❑ **Gas Requirements** - Supply proper gas piping size to this water heater 1 inch (2.5 cm) NPT or equivalent is required for 399,999 btu/hr (116.8 kw) model and 499,999 btu/hr (146.5 kw) model. Install a properly sized regulator to supply an adequate volume of gas. 7 inches (1741.9 Pa.) W.C. of gas is required when the water heater is operating. Gas pressure must stay below 14 inches (3483.8 Pa) W.C. when unit is in standby. Pressure drop between non-operating and operating pressures should be less than 3 inches (746.5 Pa) W.C.
- ❑ **Condensate Requirements** - Condensate line must be properly sized and sloped to a suitable drain (¼ inch per foot (.6 cm per .3 m)). A condensate trap must be constructed as close to the water heater as possible. Protect the condensate line from freezing conditions. Use rubber coupler, p/n 239-53385-00, included with this water heater to connect condensate line to condensate elbow as show below. See instruction manual for full condensate trap assembly starting on page 7.



Apply clear RTV sealant around the entire circumference of the male end of exhaust pipe before installing the female end of the condensate elbow as shown above. Then pull forward vent adapter, p/n 239-53384-00 and tighten hose clamps to ensure no leaks.

- ❑ **Service / Mechanical Room** - Provide adequate space for servicing the heater. Leave room to get to the bottom pressure switch as well as enough overhead room to remove the power anode rods for servicing (18 inch (45.7 cm) min.).

Maximum Venting Lengths (Combined) (Max. Vent = Exhaust + Intake)

| Model Numbers | 4 inch (10.2 cm) PVC, ABS & CPVC | 6 inch (15.2 cm) PVC, ABS & CPVC |
|---------------|-------------------------------------|-------------------------------------|
| EF-120T-400 | 120 feet (36.6 m) | 240 feet (73.2 m) |
| EF-120T-500 | 120 feet (36.6 m) | 240 feet (73.2 m) |

NOTE: 4 inch (10.2 cm) & 6 inch (15.2 cm) 90° Elbows = 5 feet (1.5 m) of pipe
4 inch (10.2 cm) & 6 inch (15.2 cm) 45° Elbows = 2.5 feet (.7 m) of pipe

For more detailed information, read the installation and operation manual provided with this water heater.

Questions? Contact Bradford White Technical Service at (800) 334-3393.