



## AQUAWASH® 2.0 SPALET® BIDET SEAT

### Questions and Answers

---

#### Warranty

##### What is the warranty?

There is a three year warranty on all parts of the SpaLet for residential applications and a two year warranty on parts for commercial applications. Terms and conditions apply.

---

#### Install

##### Is a professional plumber required for installation?

The bidet seats itself is very simple to install and much like a regular toilet seat with the addition of a water hose and tee connector. You can have a professional plumber do it, but many people prefer to install it themselves.

##### What type of power is needed?

AC120V GFCI outlet. The seat consumes 1000W.

##### What type of water pressure is needed?

Minimum Inlet Water Pressure is 10 psi/0.07 MPa Flow Pressure  
Maximum Inlet Water Pressure is 108 psi/0.75 MPa Hydrostatic Pressure

##### Does this bidet seat fit my toilet?

The bidet seat fits most elongated toilets; please refer to the fit chart in the installation manual.

##### Do you need to buy anything else for installation?

Items needed for installation include standard household tools such as an adjustable wrench, Phillips and flat head screw driver.

---

#### Components

##### What comes with the product?

The following parts are included in the product:

- Seat unit (seat ring, seat lid and power cord)
- Mounting plate
- Manual
- Mounting bolts, brackets, nuts and bushings (2 pieces each)
- Seat unit water supply hose (with filter)
- Junction valve

##### Is the remote included in the product?

No, this is a side dial manual operation bidet seat without a remote.

---

#### Dimensions

##### What is dimension of the product?

The dimension of the product is 14-7/16" (367 mm) (W) x 20" (508 mm) (D) x 3-3/4" (95 mm) (H).

##### What is the size of the seat opening?

The inner diameter of the seat is 8-1/16" (205 mm) wide and 11-13/16" (300 mm) long.

##### How long is the power cord?

Effective length 42" (1067 mm).

---

#### Functions and Features

##### How does the self-cleaning nozzle work?

Once the user presses the spray function, the automatic self-cleaning nozzle function rinses the nozzles prior to opening the nozzle shutter door and extending the nozzles. This function cleans the nozzle and surrounding area before and after use of the back cleansing and front cleansing features.

**What is a nozzle shutter?**

The nozzle shutter is the door that covers the nozzles. This provides an additional level of hygiene by preventing waste or debris from contacting the nozzle tips.

**What are the main features?**

- Heated seat (2 temperature levels).
- Dual, adjustable, self-cleaning water sprays for independent front and back cleansing.
- Adjustable water pressure control setting.
- Instant heat for on demand warm water.
- Soft night light for soothing guide at night.

**Does this SpaLet® bidet seat have Pre-Mist?**

No, the AquaWash® 2.0 SpaLet bidet seats do not have a Pre-Mist function.

**How long is the spray cycle?**

The spray will continuously run until the dial is set back to the 90 degree position(OFF).

**How much water is used during the spray cycle?**

0.7 L/min at a water pressure of 0.18 MPa is used during the spray cycle.

**How long is the drying cycle?**

There is no dryer function on AquaWash 2.0 SpaLet bidet seat models.

**How many different water temperature settings are available?**

2 different levels of water temperature settings are available.

**How many seat temperature settings are available?**

2 different levels of seat temperature settings are available.

**How many water pressure settings are available?**

The water pressure is adjusted by the side dial. The more you turn the dial the higher the pressure would be.

**What are the different spray patterns?**

There is 2 different spray patterns of back cleansing and front cleansing.

**What is the temperature of the heated seat?**

The seat temperature has a 2 setting of:

Low setting – approx. 91.4°F / 33°C.

High setting – approx. 98.6°F / 37°C.

**What is the temperature of the water?**

The water temperature has a 2 setting of:

Low setting: about 95°F / 35°C.

High setting: about 100°F / 38°C.

**Does this have an automatic seat? Slow-close seat?**

The AquaWash 2.0 SpaLet bidet seat does have a slow-close seat and lid for user convenience but does not have an automatic open/close lid.

**How does the bidet work?**

The bidet will work by turning the dial towards front or back from the 90 degree position. It will function without electricity and without a person sitting on it. Though as a safety sensor a high pitch sound will beep when the spray is operated while no one is seated.

**How long does the heated seat stay warm?**

The heated seat will stay warm as long as the seat temperature is set to "Low" or "High" setting. Though as a protection feature it will automatically turn the seat temperature from "High" to "Low" when seated for 5 minutes or more under the "High" temperature setting.

**How much electricity does this consume?**

The AquaWash® 2.0 SpaLet® bidet seat has a rated power consumption of 1000W.

**How does the heated water supply work, where do I get the warm water from?**

The incoming water is transferred through an instant water heating element that keeps the water warm on a continuous basis during use.

**How long does the heated water last for?**

The heated water is available on demand. It will not run out.

**Where does the water come from that the bidet function uses?**

The clean water comes from the incoming water supply line. Tank water is NOT used for the bidet function.

**Does this toilet have a nightlight?**

Yes, the AquaWash 2.0 does have a night light function for soothing guide at night.

**Is there a child lock out feature?**

There is no specific child lock out feature but we do have a seat sensor that makes a high pitch sound to alert when a spray function is operated while no one seated.

**What side is the dial on?**

The spray functioning dial is situated to your right side when sitting down and is connected to the seat. On the other side the water and seat temperature adjustment button is located. This cannot be relocated or changed.

---

**How to Use****What type of maintenance is required/recommended?**

- Cleaning of the seat can be achieved by using a cloth and a non-chlorinated cleaner.
- Cleaning the nozzle tips: First close the shut-off valve then pulled out the whole nozzle with your hand. From there pull the nozzle tip straight towards yourself to detach it. Use a soft bristle toothbrush to clean it.
- Cleaning the nozzle shutter.

**Is this product suitable for children?**

When small children are using this product, ensure that the proper operating procedures are followed at all times to ensure the user's safety.

**How do I clean this product?**

You can clean the seat by using soft cloth and non-chlorinated cleaner.

---

**Other****Where is it manufactured?**

The AquaWash 2.0 SpaLet bidet seats are manufactured in China.

**Could you use it outside North America?**

This product is designed for use in the USA and Canada. Please refer to the product specifications chart in the installation manual for electrical and water requirements.