


SUBMITTAL DATA SHEET

NL Ball Style Corporation Stop - 74701BL

AWWA/CC x Copper Flare Less Flare Nut



MODEL	SIZE	A	B	C	D	E	F
74701BL	3/4	4.65	1.96	.75	1.39	3/4	3/4
74701BL	1	4.60	2.11	1.00	1.50	1	1
74701BL	1 1/4	6.53	3.02	1.25	1.88	1 1/4	1 1/4
74701BL	1 1/2	6.80	3.05	1.50	2.15	1 1/2	1 1/2
74701BL	2	7.56	3.21	2.00	2.46	2	2

SUBMITTAL INFORMATION

- Manufactured in compliance with ANSI/AWWA C800 (latest revision)
- Brass components in contact with potable water conform to ASTM B584, UNS C89833 (latest revision) and identified with "NL"
- Certified to NSF/ANSI 61 and NSF/ANSI 372
- Brass components not in contact with potable water conform to ASTM B62 and ASTM B584, UNS C83600 -85-5-5-5 (latest revision)
- PTFE coated brass ball rotates 360°
- Rated for 300 PSIG water pressure
- Blow out proof EPDM port seals
- End piece joint sealed with an EPDM o-ring and thread locker



A.Y. McDonald Mfg. Co.
P.O. Box 508
Dubuque, IA 52004-508

Toll Free: 1-800-292-2737
Fax: 1-800-832-9296
Hours: 7:00 a.m. - 5:00 p.m., CST

sales@aymcdonald.com
www.aymcdonald.com

A.Y. McDonald considers the information on this assembly drawing correct when published. Item and option availability, including specifications, are subject to change without notice.

Submitted by:

10-14