

General Product Specification

| Item No. | OSSK-95 |
|----------|---------|
|----------|---------|

| Date | 6/12/2017 | No. Pages | 1 | ı |
|------|-----------|-----------|---|---|
|------|-----------|-----------|---|---|

Product Description:

| Style | Oil Only Spill Kit |
|------------------|---|
| Item Size (each) | N/A |
| Color | N/A |
| Composition | 100% Polypropylene |
| Structure | Contains: 12- 3" x 4' socks, 110- 15" x 18" pads, 8 - 3" x 12' socks, 8 - 18" x 18" pillows, 10 - disposal bags with ties, 1 - pair nitrile gloves, 1-pair goggles, 1 emergency hand book, packaged in a 95 Gallon Overpack |
| Technology | Meltblown |
| Absorbency | Oil Only (Hydrophobic) |
| Bonding | N/A |

| Intended Application | Oil Only (Hydrophobic) absorbent |
|----------------------|----------------------------------|
|----------------------|----------------------------------|

| Absorbency Capacity | 75.0 gallons per kit |
|---------------------|----------------------|
|---------------------|----------------------|

Packaging Description:

| Packaging Configuration | each |
|-------------------------|------------------|
| Items Per Package | 1 Oil Only Spill |
| | Kit/each |
| Container Type | 95 Gallon |
| | Overpack |

| Package Weight | 75.0 lbs |
|---------------------------|--------------------|
| Package Dimensions | 31.5" x 31.5"x 35" |
| | |
| | |
| | |

Physical Properties:

| Parameter | MBT Test Method | Units | Nominal | (+/-) Tolerance |
|------------------------|-----------------|-------|---------|-----------------|
| Basis Weight | MBTTM001 | LBS | 75.0 | 6 |
| Absorbency** (med Oil) | MBTTM012 | GAL | 75.0 | 7 |
| 3" Tensile Strength | MBTTM02 | LBS | N/A | N/A |
| Color | N/A | | | |

The above properties are "nominal" values used for process control when the product is produced and/or inspected. Performance "nominals" may very depending upon the specific application, and/or environment being applied, stored, or shipped.

** The "Absorbency" spec and "MBTTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

| Attributes | Product will be free of foreign material contamination, rips, holes and | |
|---------------|---|--|
| | tears. | |
| Labeling | | |
| Certification | Make no changes in basic process or composition without notifying | |
| | customer. | |