

Product Specifications

Model Family	MSK60
Typical Application:	Sewage, dewatering
Capacities:	up to 130 GPM (8.2 LPS)
Heads:	up to 28 ft (8.5 m)
Electrical:	115V, 1 ϕ , 12.0 FLA, 60Hz; 208V, 1 ϕ , 6.9 FLA, 60Hz; 230V, 1 ϕ , 6.0 FLA, 60Hz; 208V, 3 ϕ , 2.9 FLA, 60Hz; 230V, 3 ϕ , 2.5 FLA, 60Hz; 460V, 3 ϕ , 1.3 FLA, 60Hz; 575V, 3 ϕ , 1.04 FLA, 60Hz
Motor:	(single phase) - 6/10 HP split phase with thermal overload protection, 1750 RPM; (three phase) - 6/10 HP polyphase, 1750 RPM
Intermittent Liquid Temperature:	140°F (60°C)
Minimum Recommended Sump Diameter:	Simplex = 24" (609.6 mm); Duplex = 36" (914.4 mm)
Automatic Operation:	Diaphragm pressure switch (single phase only, manual available)
Materials of Construction:	Class 30 cast iron
Impeller:	Class 30 cast iron two-vane nonclog
Discharge Size:	2" NPT (50.8 mm); 3" NPT (76.2 mm) optional
Solids Handling:	2" (50.8 mm)
Power Cord:	1 ϕ , 115V - 10', STW-A (20' optional); other 1 ϕ and all 3 ϕ - 20', STW-A

Performance Curve

