

Location:




SYMMONS® Dia™

Tub-Shower System 3502-CYL-B

Specification Submittal



Feature Highlights

- Symmons Tub-Shower System with Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Screwless brass escutcheon (-B)
- Cylinder (-CYL) style lever handle
- Showerhead, single mode #352SH
- Mounting bracket and flange for showerhead
- Standard flow rate is 2.5 gpm (9.5 L/min)
Optional lower flow rate restrictor available 
- Tub-spout with diverter, 7 inches #352TS
- Polished chrome finish (standard)

Model Numbers

- ☐ 3502-CYL-B
Tub-Shower System with Symmons Temptrol® mixing valve p/n 4000-BODY
- ☐ 3502-CYL-B-TRM
Trim only, valve must be ordered separately
- ☐ 4000-BODY
Symmons Temptrol® mixing valve without trim
- ☐ 4000-X-BODY
Symmons Temptrol® valve without trim. Valve includes integral service stops to allow water shut-off for service

Finish Options / Modifications

Append appropriate -suffix to model number

- ☐ -STN Satin nickel
- Polished chrome (standard finish)

Standards / Certifications



ASME A112.18.1-2005 / CSA B125.1-05
Americans with Disabilities Act (ADA) compliant

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

Options / Modifications

Append appropriate -suffix to model number

- ☐ -IPS IPS connections: 1/2 inch female IPS connections on Temptrol® mixing valve
- ☐ -X Service Stops: Temptrol® mixing valve includes integral service stops to allow water shut-off for service, p/n 4000-X-BODY (Available when ordering model 3502-CYL-B)
- ☐ -CHKS Check Stops: Temptrol® mixing valve includes integral check stops (Requires integral service stops, suffix -X. Used in installations where a positive shut-off device is used downstream of mixing valve.)
- ☐ -REV Reverse core: Temptrol® mixing valve with reverse core. (Requires integral service stops, suffix -X. Used in back-to-back system installations. HOT on the right, COLD on the left)
- ☐ Delete Suffix B Chrome plastic escutcheon chrome plastic escutcheon is supplied instead of standard brass escutcheon
- ☐  -2.0 Flow rate restrictor, 2.0 gpm (7.6 L/min)
- ☐  -1.5 Flow rate restrictor, 1.5 gpm (5.7 L/min)
- ☐ -L/HD Showerhead not included, Includes mounting bracket and flange
- ☐ 352SH-3 Showerhead is three-mode in place of standard single mode
- ☐ -SS Slip-on diverter tub spout instead of standard tub spout

Handle Options / Modifications

Append appropriate -suffix to model number



- ☐ -LR Lever handle
- ☐ -LP Loop style lever handle

Dimensions Dia Tub-Shower System, 3502-CYL-B

