

SPECIFICATIONS

FIGURE IS4CT4 - IS6CT4

STAINLESS STEEL FITTINGS



304 & 316 STAINLESS STEEL THREADED 45

PRODUCT SPECIFICATIONS

- The material composition and quality requirements shall comply with ASTM A351/A351M
- Threads should be in accordance with ASME B1.20.1-1983



REFERENCE CHART

Item #	Size (in.)	A	L	Grade
IS4CT4A	1/8	0.630	0.728	304
IS4CT4B	1/4	0.728	0.748	304
IS4CT4C	3/8	0.886	0.748	304
IS4CT4D	1/2	1.181	0.866	304
IS4CT4F	3/4	1.398	0.906	304
IS4CT4G	1	1.752	1.102	304
IS4CT4H	1-1/4	2.047	1.260	304
IS4CT4J	1-1/2	2.343	1.378	304
IS4CT4K	2	2.835	1.752	304
IS4CT4L	2-1/2	3.425	1.850	304
IS4CT4M	3	4.173	2.047	304
IS4CT4P	4	5.039	2.598	304
IS6CT4A	1/8	0.630	0.728	316
IS6CT4B	1/4	0.728	0.748	316
IS6CT4C	3/8	0.886	0.748	316
IS6CT4D	1/2	1.181	0.866	316
IS6CT4F	3/4	1.398	0.906	316
IS6CT4G	1	1.752	1.102	316
IS6CT4H	1-1/4	2.047	1.260	316
IS6CT4J	1-1/2	2.343	1.378	316
IS6CT4K	2	2.835	1.752	316
IS6CT4L	2-1/2	3.425	1.850	316
IS6CT4M	3	4.173	2.047	316
IS6CT4P	4	5.039	2.598	316

