

SPECIFICATIONS

FIGURE IS4CTC - IS6CTC

STAINLESS STEEL FITTINGS



304 & 316 STAINLESS STEEL THREADED COUPLING

PRODUCT SPECIFICATIONS

- The material composition and quality requirements shall comply with ASTM A351/A351M
- Threads should be in accordance with ASME B1.20.1-1983



REFERENCE CHART

| Item # | Size (in.) | L | B | L1 | Grade |
|---------|------------|-------|-------|-------|-------|
| IS4CTCA | 1/8 | 1.000 | 0.551 | 0.315 | 304 |
| IS4CTCB | 1/4 | 1.000 | 0.728 | 0.394 | 304 |
| IS4CTCC | 3/8 | 1.122 | 0.846 | 0.433 | 304 |
| IS4CTCD | 1/2 | 1.382 | 1.047 | 0.571 | 304 |
| IS4CTCF | 3/4 | 1.500 | 1.252 | 0.591 | 304 |
| IS4CTCG | 1 | 1.622 | 1.555 | 0.669 | 304 |
| IS4CTCH | 1-1/4 | 2.000 | 1.909 | 0.827 | 304 |
| IS4CTCJ | 1-1/2 | 2.122 | 2.165 | 0.827 | 304 |
| IS4CTCK | 2 | 2.500 | 2.622 | 0.945 | 304 |
| IS4CTCL | 2-1/2 | 2.870 | 3.327 | 1.181 | 304 |
| IS4CTCM | 3 | 3.181 | 3.957 | 1.220 | 304 |
| IS4CTCP | 4 | 3.681 | 5.098 | 1.417 | 304 |
| IS6CTCA | 1/8 | 1.000 | 0.551 | 0.315 | 316 |
| IS6CTCB | 1/4 | 1.000 | 0.728 | 0.394 | 316 |
| IS6CTCC | 3/8 | 1.122 | 0.846 | 0.433 | 316 |
| IS6CTCD | 1/2 | 1.382 | 1.047 | 0.571 | 316 |
| IS6CTCF | 3/4 | 1.500 | 1.252 | 0.591 | 316 |
| IS6CTCG | 1 | 1.622 | 1.555 | 0.669 | 316 |
| IS6CTCH | 1-1/4 | 2.000 | 1.909 | 0.827 | 316 |
| IS6CTCJ | 1-1/2 | 2.122 | 2.165 | 0.827 | 316 |
| IS6CTCK | 2 | 2.500 | 2.622 | 0.945 | 316 |
| IS6CTCL | 2-1/2 | 2.870 | 3.327 | 1.181 | 316 |
| IS6CTCM | 3 | 3.181 | 3.957 | 1.220 | 316 |
| IS6CTCP | 4 | 3.681 | 5.098 | 1.417 | 316 |

