


Submitted Model No.: \_\_

Specific Features:



#### ▲ Designate proper finish suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-L-548LF-MPU Rev. B



see what Delta can do

# **BATHROOM FAUCET**

- Bowery<sup>™</sup> Collection
- Single Handle Deck Mount

### **STANDARD SPECIFICATIONS:**

- Max. flow rate 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa
- Order aerator RP100693-1.0 for maximum 1.0 gpm @ 60 psi, 3.8 L/min @ 414 kPa
- Order aerator RP92901-0.5 for maximum 0.5 gpm @ 60 psi, 1.9 L/min @ 414 kPa
- Solid brass cast body
- One or three hole mount (escutcheon optional, included)
- Polymer braided flexible supply hoses with 3/8" compression fitting - 29" (730 mm) long
- Diamond coated ceramic cartridge
- Handle motion "Euro Style"
- Red / blue temperature indication
- Models have metal drain with pop-up type fitting with plated flange and stopper

## WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



## **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2

Indicates compliance to

ICC / ANSI A117.1 - Valve control only

EPA WaterSense<sup>®</sup>

**Delta Faucet Company** 55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON NSP 4L1 © 2020 Delta Faucet Company