

# PlumBite® Push On Ball **Valve**

#### **Specifications**

• A heat-free method of joining Copper, CPVC, PE-RT or PEX tubing. Fittings can be removed and re-used, using the disassembly tool (sold seperately).

#### **Applications**

• Commercial and residential potable and non-potable water applications

**NOTE:** Not for use with PEX-AL-PEX or PEX tubing with an oxygen barrier. NOT FOR USE AT OR BELOW GROUND LEVEL.

#### **Materials**

- Gasket- EPDM, Peroxide Cured
- Valve Body- Brass
- Handle-Steel

## Job Name Location \_\_\_\_\_ Engineer \_\_\_\_\_ Contractor \_\_\_\_\_ \_ PO#\_\_\_ Tag \_\_



#### **Dimensions and Product Offering**

Part Code	<b>Bulk Part Code</b>	Size	A -(in.)	B -(in.)	C -Nominal (in.)	D -(in.)	D -Tolerance +/- (in.)
C77460LF	C76561LF	1/2	3.62	1.69	1/2	2.93	0.08
C77461LF	C76562LF	3/4	3.62	1.91	3/4	3.42	0.17
C77462LF	-	1	4.17	2.40	1	3.97	0.18
C77463LF	-	1-1/4	4.29	2.91	1-1/4	5.15	0.12
C77464LF	-	1-1/2	5.61	3.13	1-1/2	5.87	0.12
C77465LF	_	2	5.61	3 43	2	6.38	0.12


#### **Performance Specifications**


- Maximum Temperature: 180°F
- Maximum Pressure: 200 PSI
- Service: Potable Water
- Exposure to water with elevated levels of inorganic materials (including but not limited to: Cl, Na, Mg, Ca, K), especially in high temperatures and high water velocity areas, could quicken the corrosion process.

#### **Certifications/Listings/Approvals**

- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372
- NSF/ANSI 14
- ASME A112.4.14/CSA B125.14:22
- IAPMO/ANSI Z1157-2014e1
- MASS Approved
- Vermont Act 193 Compliant











## Small Ball Valves 0.50" to 1.00" Exploded View



REF NO.	DESCRIPTION	MATERIAL	QTY
1	HANDLE NUT	STAINLESS STEEL (S201)	1
2	HANDLE	CHROME PLATED STEEL (Q235)	1
3	PACKING GLAND	BRASS	1
4	STEM PACKING	PTFE	1
5	STEM	LEAD FREE BRASS (C46500)	1
6	TUBE SUPPORT	PSU or POM	2
7	PROTECTOR	РОМ	2
8	RELEASER	POM	2
9	GRIPPER RING	STAINLESS STEEL (300 series)	2
10	LOCK RING	POM or PA66	2
11	O-RING	EPDM	2
12	END CAP	LEAD FREE BRASS (C46500)	1
13	SEAT SEAL	PTFE	2
14	BALL	LEAD FREE CHROME PLATED BRASS (C46500) SIZES 1/2" & 3/4"	1
15	BODY	LEAD FREE BRASS (C46500)	1
16	REMOVAL TOOL	POM	1

### Large Ball Valves 1.25" to 2.00" Exploded View



REF NO.	DESCRIPTION	MATERIAL	QTY		
1	HANDLE NUT	STAINLESS STEEL (S201)	1		
2	HANDLE	CHROME PLATED STEEL (Q235)	1		
3	PACKING GLAND	BRASS (HPB58-3)	1		
4	STEM PACKING	PTFE	1		
5	STEM	LEAD FREE BRASS (C46500)	1		
6	TUBE SUPPORT	BRASS (H62)	2		
7	PROTECTOR	BRASS (HPB58-3)	2		
8	RELEASER	BRASS (HPB58-3)	2		
9	GRIPPER RING	STAINLESS STEEL (S304)	2		
10	LOCK RING	BRASS (HPB58-3)	2		
11	O-RING	EPDM	2		
12	END CAP	LEAD FREE BRASS (C46500)	1		
13	SEAT SEAL	PTFE	2		
14	BALL	LEAD FREE CHROME PLAT- ED BRASS (C46500) SIZES 1-1/4" & 1-1/2" ONLY	1		
		STAINLESS STEEL HOLLOW BALL (S304) SIZE 2" ONLY			
15	BODY	LEAD FREE BRASS (C46500)	1		

800.355.6637 • jonesstephens.com ©2025 Jones Stephens 0725