


Zoning Solutions

Zoned Comfort Control™ Kits



- + Saves time
- + Convenient everything in one box
- + Ideal for installers in residential new construction

Kit Includes:

Zone Panel

24V 40VA Universal

6" Duct Probe

Transformer

MODEL NO.	DESCRIPTION	DIMENSIONS (H x W x L)	HUMIDITY	OPERATING TEMPERATURE	SHIPPING TEMPERATURE	VOLTAGE	MAXIMUM CURRENT	WARRANTY
6202K	Single-Stage 2-Zone Heat/Cool Zone Board w/Sensor and 24V 40VA Transformer	9 ³³ / ₅₀ " x 8 ⁶³ / ₁₀₀ " x 1 ⁴³ / ₅₀ "	5%-90% RH, non-condensing	32°F-158°F	-40°F-180°F	18-30VAC 50/60 Hz	Damper output per zone (fused): 18VA at 158°F, 30VA at 90°F zone panel and thermostats (fused): 18VA at 158°F, 30VA at 90°F zone panel consumption: 4VA max Note: Use 18 or 20 AWG solid (non-stranded) wire	S-YEAR .
6203K	Single-Stage 3-Zone Heat/Cool Zone Board w/Sensor and 24V 40VA Transformer							
6302K	Single-Stage 2-Zone Heat Pump Zone Board w/Sensor and 24V 40VA Transformer							
6303K	Single-Stage 3-Zone Heat Pump Zone Board w/Sensor and 24V 40VA Transformer							
6403K	Single or Multi-Stage 3-Zone Universal Zone Board w/Sensor and 24V 40VA Transformer	14 ¹⁸ / ₂ 5" x 8 ¹⁷ / ₂ 0" x 1 ⁴³ / ₅ 0"						
6404K	Single or Multi-Stage 4-Zone Universal Zone Board w/Sensor and 24V 40VA Transformer							