# **MERCURY** 36" Dual Fuel Range

AMC36DF

With gleaming stainless steel accents and a lustrous finish, nothing is more sublime for modern kitchen design than the AGA Mercury. A true European mastery of cooking, its performance parallels in quality for a cooking experience that satisfies your eye as well as your palate.

## **Oven Features**

**7-mode multifunction oven** with European dual-convection cooking, fan-assisted baking, browning, thaw and serve, convection broiling, warming and conventional cooking

- Spacious 4.5 cu. ft. oven capacity
- Three heavy-duty telescoping glide-out oven racks
- Dual broiler system
- EasyClean™ surface with black enamel interior

#### Cookware accessories include:

- Two roasting tins rest in the telescoping shelf and slide out with ease
- Adjustable full-width broiler pan with trivet is ideal for broiling large batches and grilling many cuts of meat

### **Cooktop Features**

**5 sealed solid brass burners** make clean-up easy and prevent messy spills from reaching the interior

- Porcelain enamel finish cast iron flame spreaders provide superb heat distribution and retention
- Powerful 17,000 BTU center burner for large pots, rapid boiling and wok cooking
- Three 12,000 BTU burners
- One 6,000 BTU simmer burner can be dialed down to 1,200 BTU
- All burners designed with thermocouple safety mechanism

**Continuous cast iron cooktop** to easily slide pots and pans from burner to burner without spilling

- Interlocking grates for secure cooking surface
- Easily removes for cleaning
- Matte finish grates won't discolor
- Hi-Fi style knobs for precise temperature control

Bottom storage drawer is large enough to hold oven racks





A: 12,000 / 2,400 BTU B: 12,000 / 2,400 BTU C: 17,000 / 3,400 BTU

D: 12,000 / 2,400 BTU E: 6,000 / 1,200 BTU







AMC36DF-SKY Midnight Sky

AMC36DF-BLK Gloss Black Matte Black





White




AMC36DF-SS Stainless Steel

# MERCURY 36" Dual Fuel Range

| General Properties Total Oven Capacity                                | 4.5 cu. ft.  |  |
|---|--|--|
| Usable Oven Space   | 28" W x 14" D x 14 ½" H  |  |
| Usable Oven Space   | Multi-function Oven with   |  |
| Cooking Mode  | 7 Cooking Modes  |  |
| Cleaning Type   | EasyClean™ Enamel  |  |
| Controls  | Knobs on fascia  |  |
| Sealed Burners  | Yes  |  |
| Cooktop Performance   |  |  |
| Cooktop Dimensions  | 35 <sup>1</sup> / <sub>2</sub> " W x 21 <sup>3</sup> / <sub>5</sub> " D          |  |
| Number of Brass Burners   | 5  |  |
| Power of Left Front Burner  | 12,000 BTU High; 2,400 BTU Low   |  |
| Power of Back Left Burner BTU   | 12,000 BTU High; 2,400 BTU Low   |  |
| Power of Center Burner BTU  | 17,000 BTU High; 3,400 BTU Low   |  |
| Power of Front Right Burner BTU                                       | 6,000 BTU High; 1,200 BTU Low  |  |
| Power of Back Right Burner BTU  | 12,000 BTU High; 2,400 BTU Low   |  |
| Electrical Details  |  |  |
| Circuit Breaker (A)   | 40A  |  |
| Volts (V)   | 240V   |  |
| Frequency (Hz)  | 60Hz   |  |
| Plug Type   | 4-prong NEMA 14-50P  |  |
| Power Cord Length   | 50″  |  |
| Energy Source   | Electric Oven and Gas Cooktop  |  |
| Gas Type  | Natural Gas<br>with LP Conversion Kit included                                   |  |
| Alternative Gas Type  | Liquid Propane   |  |
| Dimensions & Weights  |  |  |
| Appliance Dimensions  | 35 <sup>7</sup> / <sub>16</sub> " W x 28 <sup>3</sup> / <sub>4</sub> " D x 36" H |  |
| Depth with Door Open  | 44 <sup>5</sup> / <sub>16</sub> "  |  |
| Weight  | 306 lbs.   |  |
| Shipping Weight   | 390 lbs.   |  |
| Package Dimensions  | 49 <sup>1</sup> / <sub>4</sub> " W x 31" D x 46 <sup>1</sup> / <sub>2</sub> " H  |  |
| Accessories Included  | ·  |  |
|   |  |  |
| 2 roasting tins<br>1 adjustable full-width broiler<br>pan with trivet | 1 – LP conversion kit  |  |
| Warranty  | ·  |  |
| 1 Year Warranty, Entire Appliance, P                                  | arts and Labor   |  |

1 Year Warranty, Entire Appliance, Parts and Labor



| Installation Clearance Dimensions   |  |  |
|---|--|--|
| A - Gap between side of appliance and adjacent vertical surface ABOVE cooktop level       | 4 <sup>1</sup> / <sub>2</sub> ″  |  |
| B - Gap between side of appliance and adjacent vertical surface BELOW cooktop level       | <sup>3</sup> / <sub>16</sub> " (U.S.)<br><sup>1</sup> / <sub>2</sub> " (Canada)      |  |
| C - Gap between cooktop level and any horizontal combustible surface                      | 31 <sup>1</sup> / <sub>2</sub> "   |  |
| D - Maximum depth of cabinets installed above the top surface cooking sections            | 13 ″   |  |
| E - Minimum distance between horizontal surfaces<br>less than dimension C                 | 35 <sup>1</sup> / <sub>2</sub> " (U.S.)<br>36 <sup>3</sup> / <sub>8</sub> " (Canada) |  |
| F - Minmum distance between horizontal cabinets<br>and worktop surfaces adjacent to range | 18 <sup>5</sup> / <sub>16</sub> "  |  |

For complete installation instructions, visit aga-ranges.com

